

FOR NEW EQUIPMENT SALES, CALL 800.958.2555
TO SPEAK WITH AN ALTEC REPRESENTATIVE or visit us online at altec.com



DRM12

FEATURES

- Feedsense® Electronic Feed Control System
- 2 Double-Edged, Hardened Knives with 2 Knife Pockets Located at 180°
- Double-Fin Rotor Increases Airflow and Improves Discharge
- Rotor-Lock Pin Holds Drum Stationary to Increase Safety
- Hydraulic Tank with Sight Gauge, Thermometer, and In-Tank Filter
- Corrosion Resistant Powder Coat Finsh

OPTIONS

- Gas and Diesel Engine Options
- · Wheel Chocks with Holders
- Removable Cone Holder
- Flag Holders
- Debris Pusher
- Steel Battery Box
- Mounted Spare Tire (Also Available as Ship Loose)
- Strobe Light
- Radiator Guards
- Hydraulic Pressure Test Gauge
- Custom Chipper Paint Colors Available

SPECIFICATIONS	Capacity	12 in (305 mm)
	Standard Engine HP	85 HP (36 kw)
	Weight	5,310 lb (2,408 kg)
	Transport Length	14.8 ft (4.5 m)
	Operational Length	16.9 ft (5.2 m)
	Width	6.6 ft (2.1 m)
	Height	8.2 ft (2.5 m)
	Infeed Chute Size	30 h x 50 w in (762 x 1,270 mm)
	Nip Point Distance	94 in (2,388 mm)
	Feed Roller Diameter	20 in (508 mm)
	Feed Roller Opening	12 h x 17 w in (305 x 432 mm)
	Feed Motor Displacement	32.2 cu in (528 cu cm)
	Feed Rate	111 fpm (36 mpm)
	Cutting Drum Speed	2,200 rpm
	Cutting Drum Width	20 in (508 mm)
	Fuel Tank Capacity	18 gal (68.1 l)
	Hydraulic Tank Capacity	12 gal (45.5 l)



For more complete information on Altec products and services, visit us on the web at www.altec.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact an Altec representative for all available options. Altec® and the Altec logo are registered trademarks of Altec Inc. in the United States and various other countries and may not be used without permission.

© 2014 Altec Inc. All Rights Reserved.

