

| | |
|-------------------------|---|
| Manufacturer | John Deere |
| Model | Gator XUV 550 S4 |
| Engine | |
| Type | 4-cycle gas, V-twin, Dynamically tuned Carb, Overhead Valves (OHV) |
| Displacement | 570 cc |
| Power | 11.9* kW 16 hp |
| Cooling system | Air cooled |
| Drivetrain | |
| Transmission | Continuously Variable Transmission (CVT) with clutch enclosure |
| Final drive | High, Low, Neutral, Reverse Transaxle |
| Four wheel drive | Dash lever actuated four-wheel drive system with limited slip front differential, plus locking rear differential |
| Traction assist | Positive locking, mechanically actuated (hand lever operated) rear differential lock |
| Descent control | Not available |
| Maximum traveling speed | 0-28 mph (0-45 kph) High Forward, 0-21 mph (0-34 kph) Low Forward, 0-16 mph (0-26 kph) Reverse |
| Suspension | |
| Front | Fully independent dual A-Arm with adjustable coils, 9 in. (228.6 mm) travel |
| Rear | Independent; H-arm and control link with adjustable coil over shock, 8 in. (203.2 mm) travel |
| Brakes | |
| Type | 196 mm ventilated disc brakes with hydraulic 1.375 in. (34.93mm) diameter twin-piston calipers |
| Park brake | Automotive-style foot-actuated mechanical park brake system |
| Tires / Wheels | |
| Front | 25x8-12 Ancla M-T (Extreme Terrain) 4-ply rating steel wheels; 25x8-12 Terrahawk AT (All Terrain) 4-ply rating steel wheels; 25x8-12 Turf tire 4ply rating steel wheels; optional 26x8-14 Maxxis Bighorn 2.0 6-ply rating on various color alloys |

| | |
|-----------------------------------|---|
| Rear | 25x10-12 Ancla M-T (Extreme Terrain) 4-ply rating steel wheels; 25x10-12 Terrahawk AT (All Terrain) -4ply rating steel wheels; 25x10-12 Turf tire 4ply rating steel wheels; optional 26x10-14 Maxxis Bighorn 2.0 6-ply rating on various color alloys |
| Dimensions / Capacities | |
| Wheelbase | 2741 mm 108 in. |
| Dry weight | 655 kg 1444 lb |
| Length | 3708 mm with bumper 146 in. with bumper |
| Width | 1435 mm 56.5 in. |
| Height | 1880 mm 74 in. |
| Tread centers | 1220 mm 48 in. |
| Ground clearance | 236 mm minimum 9.3 in. minimum |
| Fuel capacity | 18.5 L 4.9 U.S. gal. |
| Cargo box dimensions | 82L x 120.9W x 29.7D (0.25 m3) cm 32.3L x 47.6W x 11.7D (8.9 ft3) in. |
| Cargo box capacity (weight) | 181 kg 400 lb |
| Payload capacity | 544 kg 1200 lb |
| Towing capacity | 499 kg 1100 lb |
| Hitch | Standard 2 in. (50 mm) rear receiver with optional 2 in. (50 mm) front receiver with recovery loops |
| Features | |
| Color | Green/Yellow, Olive/Black, REALTREE HARDWOODS HD Camo |
| Power steering | Not available |
| Battery / Alternator / Power port | 340 CCA 16 amp @ 4100 rpm, regulated 12 VDC standard outlet |
| Instrumentation | Digital display with hour meter with maintenance and driver seatbelt reminder; optional speedometer and engine oil temperature sensor |

| | |
|----------------|---|
| Storage | 2 cupholders, sealed underhood storage, glovebox, center console, optional under seat |
| Seating | Bench seat front/rear |
| Date collected | |

Specifications are based on published information at the time of publication. Specifications are subject to change without notice.

Prices are subject to change without notice. Prices are in dollars and only applicable to products sold in the United States. In all cases, current published price lists and incentive program bulletins will take precedence. All trademarked terms, including John Deere, the leaping deer symbol and the colors green and yellow used herein are the property of Deere & Company, unless otherwise noted.