



Occupant Side Retention

Choose from ANSI certified OSR nets (standard) or available stylish half doors. Both offer easy single handed open and closing.



Dynamic engine braking

Go downhill and be in control. It's easy with our rear wheel dynamic engine braking system.



THE FOUR-PERSON TEAM

The off-road is now even roomier. We've maximized space to accommodate a team of four. Take control of any trail with standard power steering. Choose between the 44 mph (71 km/h), 50-HP[†] (37 kW) gas powered XUV825M S4, our fastest, most powerful full-size four-seater, or the 32 mph (52 km/h) 23-HP[†] (17 kW) diesel powered XUV855M S4.

[†]The engine horsepower and torque information are provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower and torque will be less. Refer to the manufacturer's website for additional information.

XUV855

Two-Person Cockpit

XUV835

Three Across

XUV865

Three Across

XUV825 S4

Four-Person Team

XUV855 S4

Four-Person Team

4-cycle diesel	4-cycle gas, Electronic Fuel Injection (EFI)	4-cycle diesel	4-cycle gas, Electronic Fuel Injection (EFI)	4-cycle diesel
854 cc	812 cc	854 cc	812 cc	854 cc
22.8 hp ¹ (17.0 kW)	54 hp ¹ (43 kW)	22.8 hp ¹ (17.0 kW)	50 hp ¹ (37 kW)	22.8 hp ¹ (17.0 kW)
Liquid	Liquid	Liquid	Liquid	Liquid
Continuously Variable Transmission (CVT) with clutch enclosure	Continuously Variable Transmission (CVT) with clutch enclosure	Continuously Variable Transmission (CVT) with clutch enclosure	Continuously Variable Transmission (CVT) with clutch enclosure	Continuously Variable Transmission (CVT) with clutch enclosure
Two speed, oil bath	Two speed, oil bath	Two speed, oil bath	Two speed, oil bath	Two speed, oil bath
On-demand true four-wheel drive system	On-demand true four-wheel drive system	On-demand true four-wheel drive system	On-demand true four-wheel drive system	On-demand true four-wheel drive system
Positive locking, mechanically actuated (hand-operated)	Positive locking, mechanically actuated (hand-operated)	Positive locking, mechanically actuated (hand-operated)	Positive locking, mechanically actuated (hand-operated)	Positive locking, mechanically actuated (hand-operated)
Yes	Yes	Yes	Yes	Yes
0-32 hi forward, 0-15 lo forward, 0-17 reverse mph	0-45+ hi forward, 0-29 lo forward, 0-33 reverse mph	0-32 hi forward, 0-15 lo forward, 0-18 reverse mph	0-44 hi forward, 0-17 lo forward, 0-20 reverse mph	0-32 hi forward, 0-15 lo forward, 0-17 reverse mph
0-51 hi forward, 0-24 lo forward, 0-27 reverse km/h	0-72 hi forward, 0-47 lo forward, 0-53 reverse km/h	0-51 hi forward, 0-24 lo forward, 0-29 reverse km/h	0-71 hi forward, 0-27 lo forward, 0-32 reverse km/h	0-51 hi forward, 0-24 lo forward, 0-27 reverse km/h
Fully independent dual A-Arm with adjustable coils	Fully independent dual A-Arm with adjustable coils; 7.9 inches (200.7 mm) of travel	Fully independent dual A-Arm with adjustable coils; 7.9 inches (200.7 mm) of travel	Fully independent dual A-Arm with adjustable coils; 8 inches (203 mm) of travel	Fully independent dual A-Arm with adjustable coils
Fully independent dual A-Arm with adjustable coils and sway bar	Fully independent dual A-Arm with adjustable coils and sway bar; 9.1 inches (231.14 mm) of travel	Fully independent dual A-Arm with adjustable coils and sway bar; 9.1 inches (231.14 mm) of travel	Fully independent dual A-Arm with adjustable coils and sway bar; 9 inches (228.6 mm) of travel	Fully independent dual A-Arm with adjustable coils and sway bar
Front/rear hydraulic disc with twin piston front calipers	Front/rear hydraulic disc with twin piston front calipers	Front/rear hydraulic disc with twin piston front calipers	Front/rear hydraulic disc with twin piston front calipers	Front/rear hydraulic disc with twin piston front calipers
Driveline, internal wet multi-disc, hand operated	Driveline, internal wet multi-disc, foot operated (hand release)	Driveline, internal wet multi-disc, foot operated (hand release)	Driveline, internal wet multi-disc, hand operated	Driveline, internal wet multi-disc, hand operated
26x9-12 Ancla M-T (Aggressive Terrain) or 25x9-12 Terrahawk AT (All Terrain) or 27x9-R14 Maxxis Big Horn Radials (Extreme Terrain)	26x9-12 Ancla M-T (Aggressive Terrain) or 25x9-12 Terrahawk AT (All Terrain) or 27x9-R14 Maxxis Big Horn Radials (Extreme Terrain)	26x9-12 Ancla M-T (Aggressive Terrain) or 25x9-12 Terrahawk AT (All Terrain) or 27x9-R14 Maxxis Big Horn Radials (Extreme Terrain)	26x9-12 Ancla M-T (Extreme Terrain) or 27x9-R14 Maxxis Big Horn Radials (Extreme Terrain)	26x9-12 Ancla M-T (Extreme Terrain) or 27x9-R14 Maxxis Big Horn Radials (Extreme Terrain)
26x11-12 Ancla M-T (aggressive terrain) or 25x11-12 Terrahawk AT (all terrain) or 27x11-R14 Maxxis Big Horn Radials (Extreme Terrain)	26x11-12 Ancla M-T (aggressive terrain) or 25x11-12 Terrahawk AT (all terrain) or 27x11-R14 Maxxis Big Horn Radials (Extreme Terrain)	26x11-12 Ancla M-T (aggressive terrain) or 25x11-12 Terrahawk AT (all terrain) or 27x11-R14 Maxxis Big Horn Radials (Extreme Terrain)	26x11-12 Ancla M-T (Extreme Terrain) or 27x11-R14 Maxxis Big Horn Radials (Extreme Terrain)	26x11-12 Ancla M-T (Extreme Terrain) or 27x11-R14 Maxxis Big Horn Radials (Extreme Terrain)
79 in. (2007 mm)	84.5 in. (2146 mm)	84.5 in. (2146 mm)	114 in. (2895.6 mm)	114 in. (2895.6 mm)
1640 lb (743.8 kg)	1793 lb (815 kg)	1793 lb (815 kg)	1992 lb (903.5 kg)	2018 lb (915.3 kg)
116 in. (2946 mm)	127 in. (3228 mm)	127 in. (3228 mm)	154 in. (3911 mm)	154 in. (3911 mm)
62 in. (1571 mm)	63.7 in. (1618 mm)	63.7 in. (1618 mm)	62 in. (1574 mm)	62 in. (1574 mm)
75 in. (1903 mm)	78 in. (1981 mm)	78 in. (1981 mm)	75 in. (1903 mm)	75 in. (1903 mm)
51.2 in. (1300 mm)	Front: 52.8 in. (1341 mm) / Rear: 49.6 in. (1259 mm)	Front: 52.8 in. (1341 mm) / Rear: 49.6 in. (1259 mm)	51.2 in. (1300 mm)	51.2 in. (1300 mm)
11.0 in. (280 mm)	11.2 in. (284 mm)	11.2 in. (284 mm)	11.0 in. (280 mm)	11.0 in. (280 mm)
7.3 U.S. gal. (27.6 L)	11.2 U.S. gal. (42.4 L)	11.2 U.S. gal. (42.4 L)	7.3 U.S. gal. (27.6 L)	7.3 U.S. gal. (27.6 L)
45 x 12 x 52 in. (1143 x 304.8 x 1320 mm)	45 x 12 x 52 in. (1143 x 304.8 x 1320 mm)	45 x 12 x 52 in. (1143 x 304.8 x 1320 mm)	45 x 12 x 52 in. (1143 x 304.8 x 1320 mm)	45 x 12 x 52 in. (1143 x 304.8 x 1320 mm)
1000 lb (454 kg)	1000 lb (454 kg)	1000 lb (454 kg)	1000 lb (454 kg)	1000 lb (454 kg)
1400 lb (635 kg)	1500 lb (680 kg)	1500 lb (680 kg)	1400 lb (635 kg)	1400 lb (635 kg)
1500 lb (680 kg)	2000 lb (907 kg)	2000 lb (907 kg)	1500 lb (680 kg)	1500 lb (680 kg)
Standard 2-in. receiver	Standard 2-in. receiver	Standard 2-in. receiver	Standard 2-in. receiver	Standard 2-in. receiver
Green/Yellow, Camouflage, Olive and Black	Green/Yellow, Camouflage, Olive and Black	Green/Yellow, Camouflage, Olive and Black	Green/Yellow, Camouflage, Olive and Black	Green/Yellow, Camouflage, Olive and Black
Yes (XUV855M Model)	Yes (XUV835M, XUV835R Models)	Yes (XUV865M, XUV865R Models)	Yes	Yes
480 CCA / 55 amp @ 7000 rpm regulated, 660 watts	480 CCA / 55 amp @ 7000 rpm regulated, 660 watts	480 CCA / 55 amp @ 7000 rpm, regulated, 900 watts (85 amp @ 7000 rpm for HVAC units)	480 CCA / 85 amp @ 6000 rpm, regulated, 1020 watts	480 CCA / 55 amp @ 7000 rpm regulated, 660 watts
Digital Display (system diagnostic light, speed, rpm, 4WD indicator, fuel level, coolant temperature, hour meter, miles, park brake light, glow plug indicator, EPAS indicator)	Digital Display (system diagnostic light, speed, rpm, 4WD indicator, fuel level, coolant temperature, hour meter, miles, park brake light)	Digital Display (system diagnostic light, speed, rpm, 4WD indicator, fuel level, coolant temperature, hour meter, miles, park brake light, glow plug indicator)	Digital Display (system diagnostic light, speed, rpm, 4WD indicator, fuel level, coolant temperature, hour meter, miles, park brake light, EPAS indicator)	Digital Display (system diagnostic light, speed, rpm, 4WD indicator, fuel level, coolant temperature, hour meter, miles, park brake light, glow plug indicator, EPAS indicator)
2 Cup Holders, Under Hood, Glovebox	4 Cup Holders (2 additional for cab units), in dash, Under Seat (56.69 L), Glovebox (3.85 L), Optional Under Hood	4 Cup Holders (2 additional for cab units), in dash, Under Seat (56.69 L), Glovebox (3.85 L), Optional Under Hood	2 Cup Holders, Under Hood, Glovebox, Under Rear Seat	2 Cup Holders, Under Hood, Glovebox, Under Rear Seat
Bench (Available Bucket Seats)	Bench (Available Bucket Seats)	Bench (Available Bucket Seats)	Bench - Front and Rear (Available Bucket Seats in Front)	Bench - Front and Rear (Available Bucket Seats in Front)
-	Halogen - Single Beam (LED High/Low Beam for XUV835R)	Halogen - Single Beam (LED High/Low Beam for XUV865R)	-	-

¹ The engine horsepower and torque information are provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower and torque will be less. Refer to the engine manufacturer's website for additional information.