

CA Aluminum Series

Cold Water – Gasoline – Direct Drive

Pump:

Equipped with the Mi-T-M Pressure Relief Start which eliminates pressure build-up in the system (Not available on CA-4004-1MCH) ■ External bypass system allows more water into the system to protect from heat build-up (CAT and General pump models) ■ Forged brass manifold ■ Thermal relief valve ■ In-line water strainer

Frame:

Lightweight, corrosion-resistant aluminum frame and base plate with 1¼-inch tube handles ■ Patented vibration isolation plate with four rubber isolators ■ Convenient gun/wand holder ■ 13-inch flat-free tires (10-inch tires on 2400, 2700 and 3000-PSI models)

Unit Includes:

Quick connect nozzles - 0°, 15° and 25° ■ 50-foot x ¾-inch non-marking high pressure hose with quick connects ■ Professional-grade insulated trigger gun with safety lock-off

Limited Warranties:

1 year Mi-T-M unloader ■ 3 year Honda and Kohler engines ■ 7 year AR, CAT, General and Mi-T-M pumps

Certification:

Intertek - Certified to UL-1776

The CA Aluminum Series is an excellent choice for cleaning contractors who are on the move. Not only is it lightweight, it is also powerful enough to remove old and peeling paint and can clean the toughest stains from most any surface.



CA-4004-1MCH



MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	Mi-T-M NO.	UNLOADER	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CA-2403-1MMH	2400	2.4	196cc Honda GX200 OHV	Mi-T-M	3-0415	Mi-T-M, adjustable pressure	36in.	39x20.5x24.5in.	100 lb.	73 lb.
CA-2703-1MMH	2700	2.4	196cc Honda GX200 OHV	Mi-T-M	3-0415	Mi-T-M, adjustable pressure	36in.	39x20.5x24.5in.	100 lb.	73 lb.
CA-2703-1MMK	2700	2.4	208cc Kohler CH270 OHV	Mi-T-M	3-0415	Mi-T-M, adjustable pressure	36in.	39x20.5x24.5in.	100 lb.	73 lb.
CA-3003-1MAH	3000	3.0	270cc Honda GX270 OHV	AR	3-0389	Mi-T-M, adjustable pressure	36in.	42.5x23.5x24.5in.	155 lb.	105 lb.
CA-3003-1MAK	3000	3.0	277cc Kohler CH395 OHV	AR	3-0389	Mi-T-M, adjustable pressure	36in.	42.5x23.5x24.5in.	155 lb.	105 lb.
CA-3504-1MAH	3500	3.5	389cc Honda GX390 OHV	AR	3-0310	Mi-T-M, adjustable pressure	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-3504-1MGH	3500	4.0	389cc Honda GX390 OHV	General	3-0350	Mi-T-M, adjustable pressure	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-4004-1MAH	4000	3.5	389cc Honda GX390 OHV	AR	3-0310	Mi-T-M, adjustable pressure	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-4004-1MAK	4000	3.5	429cc Kohler CH440 OHV	AR	3-0310	Mi-T-M, adjustable pressure	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-4004-1MCH	4000	4.0	389cc Honda GX390 OHV	CAT	3-0451	Mi-T-M, adjustable pressure	48in.	42.5x23.5x24.5in.	178 lb.	128 lb.
CA-4004-1MGH	4000	4.0	389cc Honda GX390 OHV	General	3-0350	Mi-T-M, adjustable pressure	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector	All models	CX-0005	36-in. insulated dual lance	2400 to 3000-PSI models
851-0338	50-ft. x ¾-in. non-marking high pressure hose	All models	CX-0097	External bypass system	2400 to 2700-PSI models
AW-8400-0021	Low pressure detergent injector	All models	CX-0098	External bypass system	3500 to 4000-PSI AR pump models
			CX-0099	External bypass system	3000-PSI models