




327PT5S

Husqvarna 327PT5S is a robust pole saw with telescopic tube. The versatile cutter head makes it easy to reach even dense trees and bushes without using a ladder or cherry picker. Low weight, good balance and rear-mounted engine provide a comfortable working position and reduced exhaust fumes. The slim cutter head has adjustable and automatic chain lubrication.



TELESCOPIC TUBE

The tube has a telescopic function for quick cutting height adjustment



BALANCE FLEX

Harness with ergonomic design. Flexible suspension to reduce stress on arms in all working positions.



CHAIN TENSIONER

Fully adjustable, allows for proper chain tensioning.



REAR IMPACT GUARD

The rear-impact guard protects the engine from wear and damage.

Features

- Easy to service and maintain starter
- Adjustable, automatic chain lubrication
- Efficient air filter
- Fuel pump for easy starting
- Auto return stop switch for easy starting

Technical data

Cylinder displacement	24.5 cc
Power output	1.2 hp
Maximum power speed	8400 rpm
Maximum recommended engine speed	11000 rpm
Carburetor	Zama
Fuel tank volume	16.9 fl oz
Fuel consumption	550 g/kWh
Idling speed	2700 rpm
Spark plug	NGK BPMR7A
Electrode gap	0.02 "
Oil tank volume	0.3 US pint
Equivalent vibration level,(ahv, eq), front/rear handle, extended	2.41/5.36 m/s ²
Equivalent vibration level,(ahv, eq), front/rear handle, collapsed	3.04/3.02 m/s ²
Sound pressure level at operators ear	92 dB(A)
Sound power level, guaranteed (LWA)	102 dB(A)
Chain pitch	1/4"
Recommended bar length, min-max	10"-12"
Weight (excl. cutting equipment)	16.09 lbs
Length, extended, including cutting equipment	156.3 "

ARTICLES		
966 56 63-01	327PT5S Pole Saw	\$ 599.95

