

TORO®

TORO® DINGO® TX 700

COMPACT UTILITY LOADERS

Designed to give you more power in a compact package, the Toro® Dingo® TX 700 expands labor savings beyond just homeowner projects. This no-nonsense workhorse packs 700 lbs of rated operating capacity and a 24.5 hp diesel engine, in a smaller footprint, so it's ideal for projects where homeowners and contractors are working in confined spaces. It also features patented Dingo TX 1000 traction controls that are easy to use, and a dedicated stand-on platform for increased operator comfort and visibility. And with dozens of compatible attachments, it's a versatile machine you can utilize for a wider range of jobs. With just the features you need, plus the familiarity and comforts of a Toro Dingo, it's an excellent solution to tackle projects big and small and increase labor savings.

FEATURES



COMPACT DESIGN

Great for homeowners and contractors who need to access smaller spaces

TRACK SYSTEM

The Dingo TX 700 trap-tracked system, offers peace of mind and comes with either an aggressive narrow track or turf-friendly wide track option

EASY-TO-USE CONTROLS

Effortless traction controls are easy to use for all-day productivity



STAND-ON PLATFORM

A dedicated platform on a compact frame. Plus, the spring loaded auxiliary foot pedal increases foot space

TORO® DINGO® TX 700

SPECIFICATIONS

| | | DINGO TX 700 NARROW TRACK (MODEL 22351) | DINGO TX 700 WIDE TRACK (MODEL 22352) | |
|-------------------------|--|--|--|--|
| ENGINE | Engine | 24.5 HP (18 kW) Yanmar 3TNV80F | | |
| | Air Filter | Remote single element | | |
| | Cooling System | Combo downflow radiator and oil cooler | | |
| | Fuel Tank | 5.5 gallons (20.8 liters) | | |
| | Oil Capacity | 3.6 quarts (3.4 liters) | | |
| HYDRAULIC SYSTEM | Hydraulic Pressure | 3,000 PSI | | |
| | Hydraulic Flow | Traction: 14.5 gpm (each pump) Auxiliary: 13.7 gpm | | |
| | Reservoir Capacity | 10 gallons (37.9 liters) | | |
| TRACKS | Standard | B-Tread | Turf Friendly | |
| | Traction | Dual hydrostatic pump | | |
| DIMENSIONS | Track Dimensions | 5.4" x 126.6" (13.7 cm x 321.6 cm) | 9.1" x 126.6" (23.1 cm x 312.6 cm) | |
| | Wheelbase | 39" (99 cm) | | |
| | Ground Clearance | 5.25" (13.3 cm) | | |
| | Overall Dimensions (WxLxH) With Bucket | 34.2" x 102.8" x 55.3" (86.9 x 261.1 x 140.5 cm) | 41.4" x 102.8" x 55.3" (105.2 x 261.1 x 140.5 cm) | |
| | Overall Dimensions (WxLxH) Without Bucket | 34.2" x 82" x 55.3" (86.9 x 208.3 x 140.5 cm) | 40.2" x 82" x 55.3" (102.1 x 208.3 x 140.5 cm) | |
| | Maximum Operating Height | 97" (246.4 cm) | | |
| | Hinge Pin Height | 73.5" (186.7 cm) | | |
| | Dump Height | 52.9" (134.4 cm) | | |
| | Dump Angle | 42-degrees | | |
| | Reach - Fully Raised | 31" (78.7 cm) | | |
| | Ground Speed | 4.5 mph (7.2 km/h) | | |
| | Weight | 2,514 lbs (1140 kg) | 2,602 lbs (1180 kg) | |
| | Tip Capacity | 2,182 lbs (990 kg) | 2,182 lbs (990 kg) | |
| | Rated Operating Capacity (35% of Tip Capacity)* | 764 lbs (347 kg) | 764 lbs (347 kg) | |
| | Ground Pressure | 6.4 PSI | 4.8 PSI | |

*Per ISO 14397-1

©2023 The Toro Company 490-0792

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligation. See your dealer for details on all of our warranties. toro.com/dingo



Count on it.