

Ventilation Equipment Non-hazardous Location



FEATURES

- ETL & CE agency certifications
- Variable speed up to 6,000 CFM
- Balanced blades to minimize vibration & movement
- Corrosion-proof, damage resistant housing
- Integral, steel wire safety screens
- Integral GripStop™ to prevent movement on inclines
- Flip-N-Store™ easy to use cord storage
- Stackable, lightweight, compact, transportable

EBF30 TEMP-BUST-R® VENTILATION FAN

The Model EBF30 TEMP-BUST-R is an excellent choice for a variety of ventilation and climate control applications such as events, trench and general construction, industrial, general demolition, oil and gas and other work environments. Use to heat and cool jobsites for increased productivity or to evacuate dust, fumes and other contaminants. The unit comes with a direct drive, variable speed motor producing 4200 to 6000 CFM for high volume air circulation. Integral handles are positioned for convenient loading and unloading from transportation vehicles and maneuvering on the jobsite. The large, 6-inch diameter wheels makes rolling over jobsite debris a breeze. Easy to activate GripStop keeps fan firmly in place when positioned on inclines during operation. Heavy-duty construction is featured throughout in the heavy-walled housing, powder coated screens, fan blades and hub to ensure quiet operation and stand up to the daily abuse in demanding environments. Convenient, built-in Flip-N-Store cord storage plus, retention straps to firmly lock units together for operating in a series for increased flow rates and when pallet stacking for transportation or storage. For use in non-hazardous environments.

SPECIFICATIONS

Power Source	.4 HP (.3 Kw), 115 VAC, 60 HZ, variable speed electric motor
Nominal Diameter	30.0 inches (762.0 mm)
Housing Construction	Double-walled, high-density, UV-resistant, polyethylene
Fan Construction	3-blade aluminum, steel hub, balanced to minimize vibration
Wheels	6.0 inch (152.4 mm) diameter
GripStop	Steel, with poly surface grips
Power Cord	18-3 SJT x 14.0 ft (4.3 M) L w/integral flip out cord storage
Agency Certifications	ETL, CE
Product Dimensions (L x W x H)	36.0 x 10.25 x 33.75 inches (914.4 x 260.4 x 857.3 mm)
Product Weight	45.1 lbs (20.5 kg)

AIR FLOW RATES & SOUND LEVELS

Description	ACFM	Sound Level (dBA)
Free Air (Low Speed)	4200.0 CFM (118.9 CMM)	78.0
Free Air (Mid Speed)	5000.0 CFM (141.6 CMM)	84.0
Free Air (High Speed)	6000.0 CFM (169.9 CMM)	90.0

All specifications are general in nature and are not intended for specific application purposes. General Equipment Company reserves the right to make changes in design, engineering, or specifications and to add improvements or discontinue manufacture at any time without notice or obligation. Consult applicable Operator Manual before utilizing. Refer to OSHA 2207 and/or current revisions for specific safety information. Names depicted are the registered trademarks of their respective owners. Sound measured at 39.4 inches (1.0 M) from face of fan.

Form: GEF03272301_v1.2