

V40 OPEN FRONT ROTARY BRUSH CUTTER

Available widths 60" & 72"

Cuts up to 3" diameter trees, and exposed blades allow faster cutting for a maintained finish.



Do not operate rotary brush cutter without a shatterproof cab door on loader.

3.0" CUT CAPACITY	60" & 72" CUT WIDTHS	16-25 GPM ONE MOTOR OPTION STANDARD FLOW ONLY	UP TO 220 LB FLYWHEEL WEIGHT	UP TO 1310 LB OVERALL WEIGHT
-----------------------------	------------------------------------	--	---	--




1. DIRECT DRIVE EATON® MOTOR WITH RELIEF VALVES

3. STANDARD MOTOR GUARD & SPINDLE GUARD

2. HYDRAULIC BRAKING STOPS FLYWHEEL IN LESS THAN 10 SECONDS

4. CIRCULAR FLYWHEEL WITH 3 UPDRAFT BLADES BOUNCES OFF STUMPS

DETAIL UNDER DECK



MODEL	BBV60-O	BBV72-O
Cut Width (in.)	60.0	72.0
Overall Width (in.)	66.0	78.0
Overall Height (in.)		21.4
Overall Depth (in.)	71.1	82.1
Deck Height (in.)		7.7
Push Bar Height (in.)		19.7
Minimum Cut Height (in.)		1.9
Cutting Capacity, Diameter (in.)		3.0
Deck Thickness: Top / Side (in.)		0.19 / 0.25*
Recommended Flow Rate (GPM)		16 - 25 Standard Flow
Approximate Weight (lbs)	1090	1310
Recommended Loader Capacity		Greater than 1500 lbs

*Material is Grade 50 Plate (50,000 PSI Minimum Yield Strength).