

Insulation Blowing Machines



POWER

- Cellulose : 1,350 lbs. / Hour
- Fiberglass : 300 lbs. / Hour
- Rockwool : 450 lbs. / Hour

SPECIFICATIONS

- Weight : 175 lbs.
- Dimensions : 20" W x 24" D x 48" H
- Hopper Capacity : 8 Cubic Feet
- Airlock : 6" x 18", Slide Gate Included
- Power : Dual Input, 115 VAC / 15 AMP
- Hose : 2-1/2" Diameter x 200'

FEATURES

- Hopper Guards
- Recessed Control Panel
- 1 HP TEFC Drive Motor
- 100' Remote Cord, Wireless Optional
- Powdercoat Finish



POWER

- Cellulose : 2,800 lbs. / Hour
- Fiberglass : 1,000 lbs. / Hour
- Rockwool : 1,600 lbs. / Hour

SPECIFICATIONS

- Weight : 290 lbs.
- Dimensions : 22" W x 28" D x 63" H
- Hopper Capacity : 14 Cubic Feet
- Airlock : 7" x 21", Slide Gate Included
- Power : Dual Input, 115 VAC / 15 AMP
- Hose : 3" Diameter x 400'

FEATURES

- Recessed Control Panel
- 1.5 HP TEFC Drive Motor
- Volt Meter, Circuit Breaker, E-Stop
- Control Panel Override Switch
- 100' Remote Cord, Wireless Optional
- Powdercoat Finish

MEYER MACHINE SUPPLY & EQUIPMENT

241 DEPOT ST. ❖ ANTIOCH, IL 60002 ❖ (800) 728-3828 ❖ Fax (847) 385-9420

www.MeyerMachine.com

SALES



SERVICE



SUPPORT