

GPS9700A 5100042221

Home >> Catalog >> Products >> Power supply >> Portable Generators >> GPS9700A



GPS9700A Material number 5100042221

Large portable generator with electric start. Versatile enough to fit any job or application.

Product details

•Unique step-start generator technology with Automatic Voltage Regulation (AVR) •Proven Honda GX340 engine with low oil shutdown.

Comes with

Includes operator's manualWheel kit

Errors and omissions are reserved. The information in this data sheet is based on present knowledge. However, this neither guarantees specific product features nor establishes a legally valid contractual relationship.

Technical specifications

GPS9700A

GENERATOR	Imperial	Metric
Phase	1 ~	1 ~
Nominal speed	3.600 1/min	3.600 1/min
Voltage accuracy	3,5 %	3,5 %
Continuous Output	9.000 W	9.000 W
Maximum Output	9.700 W	9.700 W
Voltage 1~	240 V, 120 V	240 V, 120 V
Efficiency factor 1~	1,00 cos	1,00 cos
Generator specification	AVR with Brushes	AVR with Brushes
Output frequency	60 Hz	60 Hz
Insulation class	F	F

OPERATING FLUIDS	Imperial	Metric	
Run Time (Prime Load)	6,5 std	6,5 std	
Fuel Tank capacity	9,8 gal US	37,0	
Fuel consumption (Prime load)	1,5 GPH US	5,7 L/Std	_

ENGINE	Imperial	Metric
Cylinder	2	2
Power rating max.	20,8 hp	15,5 kW
Cooling	air cooling	air cooling
Engine Manufacturer	Honda	Honda
Cylinder capacity	42,0 Inch3	688 cm3
Kraftstofftyp	Gasoline	Gasoline
Engine speed (Power max.)	3.600 1/min	3.600 1/min
Oil filling max.	0,4 gal US	1,50 l
Starter type	E-starter	E-starter
Engine type	Gasoline engine	Gasoline engine

Errors and omissions are reserved. The information in this data sheet is based on present knowledge. However, this neither guarantees specific product features nor establishes a legally valid contractual relationship.

SHIPPING AND STORAGE	Imperial	Metric
Width for shipping	28,5 "	725 mm
Shipping weight	396,8 lb	180,00 kg
Height for shipping	29,2 "	741 mm
Length for shipping	44,1 "	1.120 mm

ELECTRICAL SYSTEM	Imperial	Metric
Receptacle Type	null, null, null, NEMA5-20R,Duplex GFCI,125V,20A	null, null, null, NEMA5- 20R,Duplex GFCI,125V,20A
Circuit Breaker Amperage AC	20 A	20 A
Breaker Switch On/Off	1 Pole	1 Pole

MECHANICAL DETAILS	Imperial	Metric
Operating weight	418,9 lb	190,0 kg
Length	36,4 "	925 mm
Dry Weight	363,8 lb	165,0 kg
Height	25,0 "	636 mm
Width	26,2 "	665 mm

ENVIRONMENT DATA	Imperial	Metric
Sound level LpA	80,0 dB(A)	80,0 dB(A)

Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions. Subject to alterations and errors expected. Applicable also to illustrations. Copyright © 2023 Wacker Neuson SE

Errors and omissions are reserved. The information in this data sheet is based on present knowledge. However, this neither guarantees specific product features nor establishes a legally valid contractual relationship.