



**WACKER  
NEUSON**  
*all it takes!*

## GP5500A

5100070505

[Home](#) >> [Catalog](#) >> [Products](#) >> [Power supply](#) >> [Portable Generators](#) >> [GP5500A](#)



## GP5500A

Material number 5100070505

Portable generator power designed for construction applications or anywhere high performance, reliable power is needed.

### Product details

- Powered by Honda
- Top Quality Alternator
- Efficient Voltage Regulation

### Comes with

- Operator's Manual

## Technical specifications

### GP5500A

<b>GENERATOR</b>	Imperial	Metric
Phase	1 ~	1 ~
Voltage accuracy	6,0 %	6,0 %
Continuous Output	5.000 W	5.000 W
Maximum Output	5.500 W	5.500 W
Voltage 1~	240 V, 120 V	240 V, 120 V
Efficiency factor 1~	1,00 cos	1,00 cos
Generator specification	Brushless	Brushless
Output frequency	60 Hz	60 Hz
Insulation class	H	H

<b>OPERATING FLUIDS</b>	Imperial	Metric
Run Time (Prime Load)	8,5 std	8,5 std
Fuel consumption (Prime load)	0,9 GPH US	3,5 L/Std

<b>ELECTRICAL SYSTEM</b>	Imperial	Metric
Receptacle Type	NEMA5-20R, Duplex GFCI, 125V, 20A, NEMAL14-30R, TL, 125/250V, 30A, NEMAL5-30R, TL, 125V, 30A	NEMA5-20R, Duplex GFCI, 125V, 20A, NEMAL14- 30R, TL, 125/250V, 30A, NEMAL5- 30R, TL, 125V, 30A
Circuit Breaker Amperage AC	21 A	21 A
Number of Sockets	4	4
Breaker Switch On/Off	1 Pole	1 Pole

<b>ENVIRONMENT DATA</b>	Imperial	Metric
Sound level LpA	74,0 dB(A)	74,0 dB(A)

<b>MECHANICAL DETAILS</b>	Imperial	Metric
---------------------------	----------	--------

Operating weight	173,9 lb	78,9 kg
Length	20,6 "	523 mm
Dry Weight	126,1 lb	57,2 kg
Height	24,1 "	612 mm
Width	27,5 "	698 mm

**Please Note**

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions. Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2023 Wacker Neuson SE