



**WACKER  
NEUSON**  
*all it takes!*

## PST2 400

5000009112

[Home](#) >> [Catalog](#) >> [Products](#) >> [Pumps](#) >> [Trash Pumps](#) >> [Submersible Pumps](#) >> **PST2 400**

### PST2 400

Material number 5000009112

High performance submersible pump to handle solids up to 0.4 in for fast and reliable dewatering.



### Product details

- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

### Comes with

- Submersible Pump
- Electrical supply cable
- Operator's manual

## Technical specifications

### PST2 400

<b>MOTOR</b>	Imperial	Metric
Nominal current	5,4 A	5,4 A
Nominal speed	3.350 1/min	3.350 1/min
Nominal voltage	110 V	110 V
Nominal frequency	60 Hz	60 Hz
Nominal power	0,400 kW	0,400 kW

<b>MECHANICAL - OUTPUT DETAILS</b>	Imperial	Metric
Flow rate max.	52,8 gal/mi	200 l/min
Solid diameter max.	0,3 "	7,0 mm
Delivery height max.	39,4 Foot	12,0 m

<b>SHIPPING AND STORAGE</b>	Imperial	Metric
Width for shipping	10,0 "	255 mm
Shipping weight	29,1 lb	13,20 kg
Height for shipping	8,5 "	217 mm
Length for shipping	16,1 "	410 mm

<b>ELECTRICAL SYSTEM</b>	Imperial	Metric
Cable definition	PVC Sheath	PVC Sheath
Length Cable	19,7 Foot	6,00 m
Cable cross-section	0,0 Inch <sup>2</sup>	1,3 mm <sup>2</sup>

<b>ENVIRONMENT DATA</b>	Imperial	Metric
Temp. limit borrowed liquid	104,0 °F	40 °C
Degree of protection	68	68

<b>MECHANICAL DETAILS</b>	Imperial	Metric
Operating weight	24,9 lb	11,3 kg
Length	9,8 "	250 mm
Intake-/Pressure socket-dia.	2,0 "	50 mm
Height	12,9 "	328 mm
Width	7,3 "	185 mm

**Please Note**

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions. Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2024 Wacker Neuson SE