



**WACKER
NEUSON**
all it takes!

PSTF2 400

5000620435

[Home](#) >> [Catalog](#) >> [Products](#) >> [Pumps](#) >> [Trash Pumps](#) >> [Submersible Pumps](#) >> **PSTF2 400**



PSTF2 400

Material number 5000620435

High performance submersible pump to handle solids up to 0.4 in for fast and reliable dewatering.

Product details

- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

Comes with

- Submersible Pump
- Electrical supply cable
- Operator's manual

Technical specifications

PSTF2 400

MOTOR	Imperial	Metric
Nominal current	null, null, 5,4 A	null, null, 5,4 A
Phase	1 ~	1 ~
Nominal speed	3.321 1/min	3.321 1/min
Nominal voltage	null, null, 110 V	null, null, 110 V
Nominal frequency	60 Hz	60 Hz
Nominal power	0,400 kW	0,400 kW

SHIPPING AND STORAGE	Imperial	Metric
Width for shipping	10,0 "	255 mm
Shipping weight	36,6 lb	16,61 kg
Height for shipping	8,5 "	217 mm
Length for shipping	16,1 "	410 mm

MECHANICAL - OUTPUT DETAILS	Imperial	Metric
Flow rate max.	52,8 gal/mi	200 l/min
Solid diameter max.	0,3 "	7,0 mm
Delivery height max.	39,4 Foot	12,0 m

ELECTRICAL SYSTEM	Imperial	Metric
Cable definition	PVC Sheath	PVC Sheath
Length Cable	20,3 Foot	6,20 m
Cable cross-section	0,0 Inch ²	1,3 mm ²

ENVIRONMENT DATA	Imperial	Metric
Temp. limit borrowed liquid	104,0 °F	40 °C
Degree of protection	68	68

MECHANICAL DETAILS	Imperial	Metric
Operating weight	24,9 lb	11,3 kg
Length	10,0 "	255 mm
Intake-/Pressure socket-dia.	2,0 "	50 mm
Height	12,9 "	328 mm
Width	7,3 "	185 mm

Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions. Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2024 Wacker Neuson SE