



**WACKER
NEUSON**
all it takes!

PSTF3 750

5000620441

[Home](#) >> [Catalog](#) >> [Products](#) >> [Pumps](#) >> [Trash Pumps](#) >> [Submersible Pumps](#) >> **PSTF3 750**

PSTF3 750

Material number 5000620441

High performance submersible pump to handle solids up to 0.4 in for fast and reliable dewatering.



Product details

- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

Comes with

- Submersible Pump
- Electrical supply cable
- Operator's manual

Technical specifications

PSTF3 750

MOTOR	Imperial	Metric
Nominal current	null, null, 10,0 A	null, null, 10,0 A
Nominal speed	3.408 1/min	3.408 1/min
Nominal voltage	null, null, 110 V	null, null, 110 V
Nominal frequency	60 Hz	60 Hz
Nominal power	0,750 kW	0,750 kW

SHIPPING AND STORAGE	Imperial	Metric
Width for shipping	13,0 "	330 mm
Shipping weight	48,3 lb	21,90 kg
Height for shipping	10,2 "	260 mm
Length for shipping	19,0 "	483 mm

MECHANICAL - OUTPUT DETAILS	Imperial	Metric
Flow rate max.	60,8 gal/mi	230 l/min
Solid diameter max.	0,3 "	7,0 mm
Delivery height max.	62,3 Foot	19,0 m

ELECTRICAL SYSTEM	Imperial	Metric
Cable definition	PVC Sheath	PVC Sheath
Length Cable	32,8 Foot	10,00 m
Cable cross-section	0,0 Inch ²	2,0 mm ²

MECHANICAL DETAILS	Imperial	Metric
Operating weight	41,9 lb	19,0 kg
Length	12,5 "	317 mm
Intake-/Pressure socket-dia.	3,1 "	80 mm

Height	15,3 "	388 mm
Width	7,3 "	185 mm

ENVIRONMENT DATA	Imperial	Metric
Temp. limit borrowed liquid	104,0 °F	40 °C
Degree of protection	68	68

Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions. Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2024 Wacker Neuson SE