

# REVOLUTIONIZING CONSTRUCTION:

The Latest Excavators Boost Productivity and  
Cut Emissions with Alternative Power Options





# 2024 EXCAVATOR spec guide

By Equipment Today

## CASE



CASE Construction Equipment's lineup of 30 mini, midi, large, wheeled, specialty and electric excavators provides solutions for nearly every size and type of jobsite. The company's machines, including the new CX50D mini excavator, are built with an operator-first perspective and offer the productivity to get more done.

Model No.	Engine HP (net)	Operating Weight (lbs.)	Std. Bucket Capacity (cu. yds.)	Breakout Force (lbs.)	Max. Digging Depth (ft. in.)	Max. Reach at Grade/Ground Level (ft. in.)
CX15EV	21*	3,131	0.03	2,600	7' 2"	12' 2"
CX17C	16.8	3,910	0.04	3,490	7' 9"	12' 11"
CX26C	24.8	5,520	0.07	4,740	8' 8"	14' 11"
CX30C	24.8	6,306	0.08	4,520	8' 2"	14' 10"
CX37C	24.4	7,990	0.11	6,900	11' 3"	18' 0"
CX42D	43.3	9,259	0.14	9,667	10' 11"	18' 1"
CX50D	58.7	10,912	0.14	9,667	11' 9"	18' 10"
CX57C	66.9	12,270	0.18	9,550	13' 4"	20' 7"
CX60C	64.7	12,940	0.18	9,190	13' 1"	20' 10"
CX75C SR	53.6	17,400	0.32	12,800	15' 2"	20' 7"
CX80C	53.6	18,900	0.32	12,800	15' 4"	22' 9"
CX140E	102	28,900	0.5	20,200	19' 10"	27' 3"
CX145D SR	102	32,100	0.5	20,200	19' 9"	28' 3"
CX170E	121	38,400	0.74	25,200	21' 4"	29' 8"
CX190E	121	41,000	0.74	31,923	21' 4"	29' 8"
CX220E	162	50,000	0.84	27,700	21' 7"	32' 6"
CX245D SR	160	56,900	0.84	31,800	21' 10"	30' 1"
CX260E	179	56,900	1.25	36,420	24' 4"	33' 9"
CX290D MH	177	72,100	N/A	N/A	11' 11"	16' 5"
CX300E	259	67,000	1.36	39,342	24' 10"	35'
CX350D	268	82,483	1.75	51,639	26' 8"	36'
CX365E SR	205	78,600	1.36	39,340	24' 5"	34' 8"
CX490D	362	109,300	2.69	55,500	30' 2"	38' 6"
CX500D ME	362	111,800	3.03	70,400	21' 4"	34' 7"
CX750D	460	158,300	3.62	68,790	21' 4"	42' 11"
WX140E	173	32,899	0.56	25,178	18' 11"	29' 3"
WX160E	173	41,360	0.81	28,325	20' 6"	30' 6"
WX155E	173	39,882	0.56	25,178	17' 4"	27' 3"
WX175E	173	44,088	0.81	28,325	18' 3"	28' 11"
WX210E	173	52,922	1.2	36,869	31' 4"	31' 4"

\* Electric motor

## KATO



The KATO compact excavator line offers versatile and durable mini excavators designed for power and precision. Known for reliability, these compact machines excel in landscaping, construction and any project. Featuring technology, maneuverability and performance, the KATO mini excavators are engineered for precision and optimal operation.

Model No.	Engine HP (net)	Operating Weight (lbs.)	Std. Bucket Capacity (cu. yds.)	Breakout Force (lbs.)	Max. Digging Depth (ft. in.)	Max. Reach at Grade/Ground Level (ft. in.)
9VXB (Battery)	48 volt	2,375	0.03	2,360	5' 2"	9'
9VXE (Electric)	*208-480 (3-phase) 240 (single-phase)*	2,060	0.03	2,360	5' 2"	9'
17VXE-Electric	480 (3-phase)	3,583	0.06	4,842	7' 2"	11' 10"
17VXB-Battery	72 volt	4,215	0.06	4,842	7' 2"	11' 10"
HD9V5*	10	2,312	0.03	2,360	5' 1"	9'
HD17V5	14	4,261	0.06	4,842	7' 2"	11' 10"
HD25V5	24	5,938	0.12	5,698	8'	13' 10"
HD30V5	23	7,084	0.12	7,065	9' 9"	15' 11"
HD35V5	23	8,082	0.14	7,688	10' 11"	17'
HD35N4	23	7,979	0.14	7,668	10' 4"	16' 2"
HD50V5	44	10,830	0.17	9,554	12' 7"	18' 5"
HD55N4	64	12,447	0.26	12,071	12' 8"	18' 10"
HD60V5	44	12,351	0.17	10,565	13' 3"	19' 3"
HD85V5	58	19,595	0.32	14,730	14' 2"	22' 8"
HD308*	67	19,750	0.4	14,803	15'	25' 7"
HD512LC-7	105	28,429	1	22,031	18' 4"	28' 8"
HD514MR-7	105	31,085	1	22,031	18' 2"	29' 8"
HD823MR-7	172	54,050	1.5	35,745	21' 1"	32' 3"

\*New Machine

## HITACHI



Hitachi Construction Machinery Americas excavators range from 3,790-pound compacts to 1,856,292-pound mining excavators. The latest ZAXIS-7 models feature large, comfortable cabs with ergonomic joysticks and operation levers that travel with the operator seat. The ZX210LC-7 to ZX350LC-7 features a TRIAS III hydraulic system to increase fuel efficiency while optimizing performance.

Model No.	Engine HP (net)*	Operating Weight (lbs.)	Std. Bucket Capacity (cu. yds.)	Breakout Force (lbs.)*	Max. Digging Depth (ft. in.)	Max. Reach at Grade/Ground Level (ft. in.)
ZX17U-5N	14.5	3,790	0.06	3,598	7' 2"	12' 2"
ZX26U-5N	20	5,560-5,890	0.11	4,994	8' 6"	15'
ZX30U-5N	23.3	6,680-7,055	0.12	6,110	9' 2"	15' 7"
ZX35U-5N	23.3	7,584-9,017	0.14 (4' 4" arm), 0.13 (5' 8" arm)	6,085	11' 4"	17' 9"
ZX50U-5N	36.8	10,560-11,729	0.18	8,267	12' 7"	20' 1"
ZX60USB-5N	53.8	13,382-14,418	0.29	9,237	13' 6"	21' 1"
ZX75US-7	64	18,100-19,800	0.37	11,263	15' 3"	22' 6"
ZX85USB-7	64	19,100-20,800	0.37	11,263	14' 10"	24' 10"
ZX130-7	100	30,870-33,951	0.59-0.77	23,380	19' 9"	28' 9"
ZX135US-7	100	31,973-35,053	0.59-0.77	23,380	19' 7"	28' 7"
ZX160LC-7	132	39,463-40,345	0.68-1.07	25,179	21' 4"	30' 7"
ZX190LC-7	132	43,652-43,880	0.67-1.19	28,551	23' 2"	32' 1"
ZX210LC-7	164	49,833-50,936	0.67-1.56	35,520	21' 11"	32'
ZX245USLC-7	164	55,669-58,212	0.67 - 1.56	35,520	21' 8"	32' 6"
ZX250LC-7	177	58,433-60,417	1.04-1.82	42,264	25'	35' 10"
ZX300LC-7	249	68,784-69,005	1.30-2.11	45,411	25' 10"	37'
ZX345USLC-7	249	76,955-79,380	1.30-2.11	45,411	24' 10"	36' 10"
ZX350LC-7	271	79,807-80,248	1.5-2.42	55,303	26' 10"	38' 11"
ZX490LC-7	388	108,027-110,672	2.7-3.3	64,295	27' 2"	41'
ZX690LC-7	465	152,340-152,340	2.9-4.0	72,838	30' 1"	45' 6"
ZX890LC-7	510	188,936 - 189,157	4.6-6.5	89,699	31' 5"	48' 11"
EX1200-7B	760	257,951	6.8	108,358	30' 9"	49' 3"
EX2000-7B	1,000	429,901	15.7	157,631	26' 7"	48' 9"
EX2000-7E	818	421,083	15.7	157,631	26' 7"	48' 9"
EX2600-7B	1,500/1,542	566,588/570,997	22.2-25.5	186,591	27' 1"	52' 8"
EX2600-7E	1,153	546,840	22.2-25.5	186,591	27' 1"	52' 8"
EX3600-7B	1,944/2,010	815,710/809,097	28.8-31.4	236,049	28' 4"	57' 11"
EX3600-7E	1,609	771,750	28.8-31.4	236,049	28' 4"	57' 11"
EX5600-7B	3,000/3,084	1,210,338/1,219,156	44.5-50.4	357,446	28' 11"	63' 8"
EX5600-7E	2,306	1,170,855	44.5-50.4	357,446	28' 11"	63' 8"
EX8000-7B	3,888/4,024	1,856,292/1,851,883	56.2-68	454,114	27' 7"	70' 3"
EX8000-7E	3,218	1,808,100	56.2-68	454,114	27' 7"	70' 3"

\*Horsepower and force measured per ISO

Note: Shovel configurations can be found in the online spec guide



# CATERPILLAR



No matter what type of work you do—excavation, trenching or truck loading—Cat excavators deliver performance, versatility and excellent fuel efficiency. Simple operation, durability and the latest safety and technology features will help you take your business to the next level.

Model No.	Engine HP (net)	Operating Weight (lbs.)	Std. Bucket Cap. (cu. yds.)	Breakout Force (lbs.)	Max. Digging Depth (ft. in.)	Max. Reach at Grade/Ground Level (ft. in.)
313	108	30,400	0.27-1.33	22,180	19' 10"	28' 5"
313 GC	73	30,400	0.27-1.33	22,180	19' 10"	28' 5"
315	108	34,000	0.27-1.33	22,180	19' 8"	28' 6"
315 GC	98	33,900	0.27-1.33	22,180	19' 8"	28' 6"
317	133	40,200	0.46-1.62	27,650	21' 8"	30' 2"
317 GC	119	38,000	0.46-1.62	27,650	21' 8"	30' 2"
320	172	49,800	0.60-2.31	36,711	21' 9"	32' 0"
320 GC	146	49,400	0.60-2.31	33,720	21' 9"	33' 2"
323	172	56,200	0.60-2.31	36,711	21' 9"	32' 0"
325	172	62,800	0.60-2.09	33,811	22' 0"	32' 1"
326	201	57,900	0.66-2.58	37,320	24' 6"	35' 2"
330	273	69,200	0.66-2.58	40,240	23' 9"	35' 0"
330 GC	201	67,900	0.66-2.58	40,240	23' 10"	35' 1"
335	273	80,000	0.68-2.58	46,482	22' 11"	34' 11"
336	300	81,100	2.97-3.53	47,190	26' 11"	38' 7"
340	346	83,100	2.97-3.53	45,390	27' 1"	38' 9"
340 (Straight Boom)	311	87,900	1.23-3.33	47,150	21' 10"	40' 6"
340 (Long Reach)	346	96,500	0.72-1.24	31,590	42' 10"	59' 4"
340 (Ultra High Demolition)	346	122,400	1.23-3.33	47,160	18' 5"	42' 3"
350	413	105,100	4.04-4.71	60,160	26' 11"	39' 10"
352	443	107,800	4.32-5.00	60,000	26' 5"	39' 9"
352 (Straight Boom)	445	114,900	4.32	60,250	18' 5"	42' 0"
352 (Long Reach)	424	128,800	0.72-1.24	31,700	42' 9"	64' 5"
352 (Ultra High Demolition)	424	143,300	1.24-4.04	60,250	18' 9"	43' 6"
374	484	162,900	4.97	80,720	31' 7"	46' 7"
395	542	207,400	5.1-6.02	86,290	35' 2"	53' 4"
M314	127	39,680	0.27-1.13	23,605	18' 4"	29' 4"
M315	145	39,680	0.27-1.13	23,830	18' 4"	29' 6"
M316	141	36,400	0.46-1.22	26,752	19' 5"	30' 3"
M318	171	43,980	0.46-1.62	26,752	20' 8"	31' 6"
M319	171	46,410	0.46-1.22	26,752	20' 2"	31' 6"
M320	171	46,740	0.50-1.62	30,799	21' 1"	32' 11"
M322	171	52,911	0.57-1.83	33,946	21' 10"	33' 5"
538 FM	172	66,140	0.72-2.08	31,588	18' 9"	32' 3"
548 FM	271	83,330	0.83-2.40	37,320	18' 9"	32' 11"
558 FM	298	91,490	0.83-2.40	40,240	22' 7"	34' 10"
568 FM	346	108,690	1.23 - 3.33	47,190	26' 1"	38' 4"

# HYUNDAI



Hyundai's HX series of compact to large crawler excavators offer power and versatile construction equipment performance with fuel-efficient, fast cycle speeds; impressive hydraulic power; and precision control. Sizes range from 4,080 pounds to 221,280 pounds with the launch of their largest model, the HX1000AL in 2024.

Model No.	Engine HP (net)	Operating Weight (lbs.)	Std. Bucket Capacity (cu. yds.)*	Breakout Force (lbs.)	Max. Digging Depth (ft. in.)	Max. Reach at Grade/Ground Level (ft. in.)
R172-9A	15.8	3,920	0.05	3,490	7' 2"	12' 7"
R252-9AK	23.2	5,640/5,690*	0.09	4,740	7' 11"	14' 8"
R302-9AK	23.2	6,380/6,625*	0.1	4,520	8' 2"	15' 3"
R352-9A	23.7	7,800/8,470*	0.14	6,900	10' 3"	17' 5"
R55-9A	65.1	12,570	0.24	9,550	12' 6"	20' 2"
R60CR-9A	63	13,450	0.24	9,190	11' 9"	20' 2"
R80CR-9A	65.1	19,290	0.37	12,570	13' 7"	22' 10"
HX35AZ	25	8,300	0.14	4,383	9' 7"	17'
HX40A	38	9,480	0.18	4,541	11' 2"	17' 6"
HX48AZ	38	10,912	0.24	5,247	11' 5"	19' 2"
HX85-A	65.1	20,608	0.37	15,338	15' 3"	23' 11"
HX130A LCR	74	29,640	0.65	24,029a	18' 6"	26' 8"
HX140A L	131	33,580	0.80	25,111a	19' 9"	28' 4"
HX145A LCR	131	34,020	0.80	25,133a	19' 6"	28' 4"
HX160A L	151	41,390	0.95	30,865a	19' 9"	29' 1"
HX180A L	152	43,610	0.95	30,865a	19' 9"	29' 1"
HX210A L	170	50,460	1.2	37,100a	21' 9"	32' 8"
HX220A L	170	51,500	1.2	37,100a	22' 1"	32' 9"
HX220A HW	170	54,540	1.2	37,100a	21' 6"	32' 9"
HX220A LR	170	54,720	0.68	18,740	38' 7"	50'
HX235A LCR	170	54,140	1.05	37,100a	22'	32' 6"
HX260A L	232	58,860	1.41	43,560a	23'	34'
HX260A HW	232	65,760	1.41	43,560a	21' 9"	34'
HX300A L	255	70,151	1.66	46,910a	24' 3"	35' 6"
HX300A HW	255	76,980	1.66	46,910a	23' 3"	35' 5"
HX300A LR	255	72,910	0.68	18,080	48' 7"	60' 9"
HX350A L	270	77,184	1.88	52,910a	24' 2"	36' 7"
HX350A HW	270	83,950	1.88	52,910a	23' 4"	36' 7"
HX355A LCR	270	78,483	1.75	39,462	22' 10"	35' 6"
HX380A L	359	88,053	2.12	56,040a	24' 8"	36' 7"
HX480A L	395	112,520	3.41	60,850a	25' 6"	39' 6"
HX520A L	395	120,704	3.41	68,780a	25'	39' 6"
HX800A L	539	181,000	4.5	85,098	27' 6"	43' 4"
HX1000A L	616	221,280	7.06	88,185	28' 10"	46' 10"
R55W-9A	65.1	12,240	0.24	9,546	11' 6"	20' 2"
HW140A	170	35,053	0.80	25,240a	16' 9"	26' 6"
HW160A	170	38,910	1.11	28,200a	18' 5"	28' 3"
HW170A LCR	170	44,181	0.80	28,150a	17' 10"	28' 8"
HW210A	173	46,690	1.05	36,860a	21' 1"	32' 1"

\*Canopy/Cab a = Powerboost



## JCB



JCB's large excavators include designs to handle tough environments; CommandPlus cabs; easy-to-use hydraulic pipework diverters, easy coupler override for larger attachment removal and advanced tool select; extended service intervals; and safety features like standard backup cameras and aluminum studded steps. The company's mid-range and compact models give operators excellent visibility and boosted power and lift with many zero-tail swing models.

Model Number	Engine hp (net)	Operating Weight (lbs.)	Max Bucket Capacity (cu. yds.)	Bucket Breakout Force (lbs.)	Digging Depth (ft.)	Digging Reach (ft.)
370X	322	87,417	3	26,460	27' 5"	38' 11"
JS160 NLC/LC MONO	125	37,997	1.3	26,438	20' 1"	29' 9"
220X LC MONO	173	51,723	1.64	33,721	20"	31' 8"
245XR LC MONO	173	55,742	1.64	33,272	21' 9"	32' 1"
131X	74	33,138	1.2	20,794	19' 11"	29' 9"
1Z141	74	35,051	1.16	20,682	19' 10"	28' 10"
150X	109	35,649	0.9	23,043	19' 11"	29"
18Z-1	23.1	3,648	customer spec	4,047	8"	12' 9"
19C-1	23.1	4,211	customer spec	4,047	8' 5"	13' 3"
19C-1E	26.6 (electric)	4,314	customer spec	4,047	8' 5"	13' 3"
35Z-1	24.7	7,840	customer spec	7,284	10' 6"	16' 6"
50Z	48.3	10,147	customer spec	8,542	11' 11"	19' 6"
55Z	48.3	11,830	customer spec	9,442	12' 7"	20"
85Z-2	64.4	18,408	customer spec	12,837	12' 1"	23' 1"
86C-2	64.4	18,960	customer spec	12,837	14' 10"	24' 3"
90Z-2	73.8	19,510	customer spec	12,837	15' 10"	24' 9"
100C-2	73.8	21,384	customer spec	16,231	16' 8"	24' 10"
Hydradig 110W	109	24,315	0.4	13,534	13' 8"	24' 5"
Pothole Pro	109	29,432	N/A	N/A	NA	24' 7"

## DEVELON



Optional around-view monitor (AVM) camera systems on DEVELON crawler excavators display a full view of the machine's surroundings, giving operators greater confidence when working in tight conditions. AVM systems offer up to 360 degrees of visibility through the monitor inside the cab, allowing operators to better identify potential hazards.

Model No.	Engine HP (net)	Operating Weight (lbs.)	Std. Bucket Capacity (cu. yds.)	Breakout Force (lbs.)	Max. Digging Depth (ft. in.)	Max. Reach at Grade/Ground Level (ft. in.)	Track (T) or Wheel (W)
DX140LC-7K	106	31,634	0.51	24,471	19' 8"	28' 0"	T
DX140LCR-7	101	34,946	0.67	24,471	19' 8"	28' 0"	T
DX200LC-7	138	50,706	1.37	36,376	20'	30' 5"	T
DX225LC-7	162	52,018	1.20	36,376	21' 7"	31' 10"	T
DX225LC-7 SLR	162	55,071	0.51	23,369	38' 3"	50' 1"	T
DX225LC-7X	162	52,018	1.20	36,376	21' 7"	31' 10"	T
DX235LCR-7	170	57,133	1.20	36,376	21' 10"	31' 7"	T
DX255LC-7	185	59,260	1.40	39,463	22' 4"	32' 10"	T
DX300LC-7	267	73,480	1.66	44,092	24' 0"	34' 7"	T
DX300LC-7 SLR	267	74,964	0.84	23,150	45' 3"	57' 5"	T
DX350LC-7	280	83,478	1.95	57,100	24' 9"	36' 0"	T
DX350LCR-7	271	79,702	1.66	47,400	23' 10"	34' 10"	T
DX420LC-7	344	103,412	2.51	64,375	25' 1"	36' 9"	T
DX490LC-7	379.5	121,678	2.80	65,920	25' 7"	38' 11"	T
DX530LC-7	379.5	121,805	3.13	67,680	24' 1"	37' 7"	T
DX530LC-7 SLR	379.5	121,168	1.20	31,965	49' 7"	63' 10"	T
DX800LC-7	547	179,431	5.80	85,098	27' 5"	42' 5"	T
DX1000LC-7	629	221,283	7.10	94,710	28' 10"	45' 11"	T
DX140W-7	129	34,194	0.77	23,303	14' 8"	24' 2"	W
DX190W-7	159	44,026	1.05	30,424	18' 9"	29' 8"	W
DX210W-7	171	50,706	1.12	34,392	19' 4"	31' 2"	W

\*SLR = Super-long reach

## JOHN DEERE



The 350 P-Tier excavator with available SmartGrade technology features improvements including a serviceable arm tip bushing and hardened pin for longer life; electronic, on-demand cooling fans; and an undercarriage design with durability improvements. The 350 P-Tier hydraulic-coupler-ready option integrates coupler controls from the factory, and the grade management path allows customers to choose their grade control solution.

Model No.	Engine HP (net)	Operating Weight (lbs.)	Std. Bucket Capacity (cu. yds.)	Breakout Force (lbs.)	Max. Digging Depth (ft. in.)	Max. Reach at Grade/Ground Level (ft. in.)
17 P-Tier	14.5	3,790	N/A	3,597	7' 2"	12' 6"
26 P-Tier	20	5,780-6,110	N/A	4,994	8' 6"	15' 2"
30 P-Tier	23	6,850-7,220	N/A	6,110	9' 2"	16' 1"
35 P-Tier	23.3	7,760-8,135	0.15	6,085	10'-11'4"	17' 1"-18' 1"
50 P-Tier	35.9	10,560-10,847	0.21	8,267	11' 7"-12' 7"	19' 7"-20' 6"
60 P-Tier	53	13,250-13,850	0.25	9,240	12' 4"-13' 6"	20' 5"-21' 6"
75 P-Tier	67.6	18,559-19,326	0.37	13,264	15' 3"	22' 6"
85 P-Tier	67.6	19,238-20,296	0.37	13,264	14' 10"	24' 10"
130 P-Tier	98	29,531-30,573	0.65	21,480	18' 2"-19' 9"	26' 11"-28' 5"
135 P-Tier	101	31,526-33,951	0.65	23,380	20'	28' 4"
160 P-Tier	122	39,526	0.78	25,180	19' 7"-21' 4"	28' 7"-30' 1"
190G W	173	43,431-45,300	1.81	28,330	19' 2"-19' 5"	30' 7"-30' 10"
200 G-Tier	146	45,170	1.31	28,552	21' 7"-23' 2"	30' 5"-32' 1"
210 P-Tier	159	51,940-53,483	1.19	35,520	21' 11"	32' 0"
245 P-Tier	159	56,879	1.43	35,520	21' 8"	32' 6"
250 P-Tier	188	60,600	1.38	42,489	22' 10"-25'	33' 2"-35' 3"
300 P-Tier	223	68,674	1.88	45,411	23' 8"-25' 10"	34' 6"-36' 5"
345 P-Tier	249	78,705	1.63	45,410	22' 8"-24' 10"	34' 11"-36' 10"
350 P-Tier	271	80,985	2.3	55,303	24' 3"-26' 10"	35' 9"-38' 3"
380 P-Tier	271	85,462	2.3	55,303	24' 3"-26' 10"	35' 9"-38' 3"
470 P-Tier	367	112,916	3.06	67,564	25' 6"-27' 2"	38' 10"-40' 3"
670 P-Tier	463	154,103	4.04	72,838-82,954	23' 4"-30'	37' 9"-44' 8"
870 P-Tier	512	188,716	4.57	89,699-106,110	23' 5"-36' 7"	39' 5"-53' 7"

## BOBCAT



The Bobcat E88 comes equipped with dual-flange track rollers, integrated counterweight and a long arm. The E88 offers fast cycle times and excellent lift capacity allowing operators to dig with confidence. Operators can enhance their machine with available options such as add-on counterweight; the Bobcat depth-check system; a Machine IQ subscription; rearview camera; widescreen touch display; and a heated, high-back seat with headrest.

Model No.	Engine HP (net)	Operating Weight (lbs.)	Std. Bucket Capacity (cu. yds.)*	Breakout Force (lbs.)	Max. Digging Depth (ft. in.)	Max. Reach at Grade/Ground Level (ft. in.)
E10	10.2	2,593	n/a	1,865	6'	10' 2"
E20	15	4,306	n/a	4,684	8'4"	14'
E26	24.8	6,489	n/a	5,652	9' 6"	16'
E32	24.8	7,403	n/a	7,284	10' 1"	16' 2"
E35 (25hp)	24.8	7,659	n/a	7,284	10' 1"	17'
E38	33.2	7,893	n/a	7,284	10' 1"	17'
E40	40.4	9,180	n/a	7,284	10' 8"	17' 10"
E48	42.6	9,830	n/a	9,601	10' 4"	17' 4"
E55	49.7	11,357	n/a	9,511	11' 4"	19' 4"
E60	55.7	12,315	n/a	10,261	13' 1"	20' 6"
E88	65.4	19,600	n/a	15,130	15' 2"	23' 6"
E145	115	34,946	n/a	24,504	19' 7"	27' 11"
E165	131	38,376	n/a	25,794	20'	28' 10"

\*Due to the variety of bucket options available on the market, this is not a category we have specs available to provide.



# STILL BREAKING GROUND

PAT. NO. 154,594  
LINK-BELT  
**150**  
YEARS  
ISSUED FEB. 5, 1874



## LINK-BELT X4S SERIES

Looking to boost your earth-moving productivity without added fuel costs? The adaptability and maximum performance of the X4S series gives you the power to tackle tough jobs. Experience our innovative line of Link-Belt excavator equipment.

**Link-Belt**  
EXCAVATORS

[LBXCO.COM/X4S](http://LBXCO.COM/X4S)



# KOMATSU



Komatsu's PC130LC-11 excavator with an 8% longer undercarriage, increases lifting capacity by up to 20% and uses up to 12% less fuel. Easily transportable, this 97.2-horsepower, small, conventional-tail-swing excavator offers a unique combination of lightweight power and agility. Durable steel castings help spread working loads away from high-stress areas for improved durability.

Model No.	Engine HP (net)	Operating Weight (lbs.)	Std. Bucket Capacity (cu. yds.)	Breakout Force (lbs.)	Max. Digging Depth (ft. in.)	Max. Reach at Grade/Ground Level (ft. in.)	Track (T) or Wheel (W)
PC30MR-5	24.4	6,836	0.07-0.21	6,631	9' 1"	16' 1"	T
PC35MR-5	24.4	8,324	0.07-0.21	6,722	11' 4"	18' 1"	T
PC45MR-5	38	11,001	0.07-0.21	7,628	11' 11"	19' 4"	T
PC55MR-5	38	11,618	0.07-0.24	8,774	12' 4"	19' 11"	T
PC78US-11	68	17,814	0.12-0.26	13,780	15' 3"	22' 8"	T
PC88MR-11	68	19,224	0.12-0.26	13,780	15'	23' 5"	T
PC130LC-11	97.2	28,660	0.34-0.78	21,000	18' 1"	26' 10"	T
PC138USLC-11	97.2	37,547	0.34-1.00	20,945	19' 4"	28' 3"	T
PC170LC-11 a	121	43,115	0.48-1.24	27,651	20' 6"	29' 9"	T
PC170LC-11 b	121	38,720	0.48-1.24	27,651	19' 7"	28' 10"	T
HB215LC-1	148	51,745	0.66-1.57	33,510	21' 9"	31' 10"	T
PC210LCi-11	165	52,639	0.66-1.57	33,510	21' 9"	31' 10"	T
PC210LC-11	165	52,639	0.66-1.57	33,510	21' 9"	31' 10"	T
PC238USLC-11	165	55,660	0.66-1.57	33,500	21' 9"	31' 10"	T
PC240LC-11	177	56,061	0.76-1.85	38,667	24'	34' 2"	T
PC290LC-11	196	71,396	0.76-2.13	44,533	23' 8"	35' 2"	T
PC290LCi-11	196	71,396	0.76-2.13	44,533	23' 8"	35' 2"	T
HB365LC-3	269	83,894	0.89-2.56	44,970	26' 10"	38' 6"	T
PC360LC-11	257	80,320	0.89-2.56	44,970	26' 10"	38' 6"	T
PC360LCi-11	257	80,320	0.89-2.56	44,970	26' 7"	38' 6"	T
PC390LC-11	257	89,940	0.89-2.91	44,970	26' 7"	38' 5"	T
PC390LCi-11	257	89,941	0.89-2.92	44,971	26' 7"	38' 5"	T
PC490LC-11	359	107,945	1.47-4.15	53,790	30' 2"	43' 3"	T
PC490LC-11 c	359	110,220	1.47-4.15	53,790	30' 2"	43' 3"	T
PC490LCi-11	359	107,945	1.47-4.15	53,790	27' 6"	40' 7"	T
PC650LC-11	436	145,284	2.05-4.98	64,150	33' 7"	47' 4"	T
PC650LC-11 SE	436	143,257	2.05-7.5	70,040	23' 2"	37' 1"	T
PC900LC-11	538	204,148	3.70-8.00	76,660	31' 11"	48' 9"	T
PC900LC-11 SE	538	211,423	8.00-10.4	81,792	23' 7"	39' 10"	T
PC1250LC-11	758	272,600	5.3-9.5	94,800	38'	56' 2"	T
PC1250SP-11	758	265,900	6-10.9	112,900	25' 11"	44' 10"	T
PC2000-11	1046	445,054	15.7-17.9	140,600	30' 4"	50' 3"	T

a = Heavy spec b = Std. spec c = Var. gauge

# LIEBHERR



Generation 8 of Liebherr crawler excavators is a leap into the future. The Gen-8 series is completely redesigned to offer customers improved performance and more operator comfort. This next generation includes higher engine power and options for a heavier counterweight and offers minimal fuel consumption. Liebherr offers technologies in the Generation 8 series such as "Modetronics," which could assist in adapting the machine to the operator's speed.

Model No.	HP (NET)	Operating Weight (lbs.)	Standard Bucket Capacity (cu. yds.)	Breakout Force (lbs.)	Max Dig Depth (ft. in.)	Max Reach at Ground Level (ft. in.)
R914 Compact	121	36,160	0.42-1.05	20,010	18' 9"	27' 8"
R920 Compact	255	46,960	0.39-1.24	22,030	18' 6"	28' 10"
R922	161	51,480	0.72-2.16	35,970	24' 1"	34'
R924	175	56,438	0.72-2.16	38,890	22' 2"	32' 5"
R926 Compact	175	57,540	0.72-1.96	31,470	22'	31' 5"
R926	201	61,290	1.50-2.29	42,040	24' 6"	34' 3"
R930	241	71,210	1.63-2.81	45,860	25' 9"	36' 3"
R934	268	81,240	1.31-3.27	50,130	26' 6"	37' 8"
R936 Compact	255	76,720	0.72-2.81	45,860	24' 11"	37'
R938	295	88,300	2.48-3.92	53,510	27' 3"	38' 5"
R945	295	103,400	2.62-3.92	53,510	27' 3"	38' 5"
R956	355	130,960	2.16-4.58	71,040	28' 3"	43'
R972	443	170,970	2.16-7.19	79,580	28' 8"	47' 1"
R992	563	212,750	2.62-8.89	109,032	30' 4"	46' 1"
A918	156	43,210	0.22-1.37	17,637	19' 6"	29' 8"
A920	175	48,281	0.72-1.57	22,188	21' 6"	32' 5"
A924	190	58,422	0.55-2.16	28,528	23' 1"	34' 7"

# KUBOTA



Kubota's compact excavators combine maneuverability, power and reliability with economy to help operators haul away more pay dirt on every job. Consisting of the KX Series and U Series, Kubota's compact excavator lineup features machines in the 1-ton to 8-ton segments with a total of 13 base models.

Model No.	Engine HP (net)	Operating Weight (lbs.)	Std. Bucket Capacity, SAE heaped min-max (cu. ft.)	Breakout Force (lbs.)	Max. Digging Depth (ft. in.)	Max. Reach at Grade/Ground Level (ft. in.)
K008-5	10.1	2,315	0.38-0.58	1,014	5' 8"	9' 11"
U10-5	10.1	2,646	0.42-0.68	1,212	5' 8"	10' 11"
U17	15.1	3,703	0.78-1.5	3,417	7' 8"	12' 8.4"
KX018-4	15.5	3,747	0.78-1.5	3,594	7' 7"	12' 9"
U27-4	20	5,625	1-3.4	5,765	9' 3.6"	15' 4"
KX033-4	23.2	7,420	2.3-4.25	8,138	10' 6"	16' 10"
U35-4	23.9	8,129	2.3-4.25	7,924	9' 8.9"	16' 11.3"
KX030-4	24.7	6,272	2.13-4.25	6,924	9' 7"	15' 9"
KX040-4	38.9	9,195	1.9-6.6	9,535	11' 2.6"	17' 9"
U48-5	38.9	10,593	3-8	9,304	10' 8"	18' 4"
U55-5	46.4	12,247	3-8	10,172	11' 11"	19' 7"
KX057-5	46.4	12,346	3-8	10,172	12' 9"	20' 1"
KX080-5	62.3	18,596	9.4-10.8	14,660	15' 1.1"	23' 6.3"

# WANT MORE?

Visit [ForConstructionPros.com](http://ForConstructionPros.com) for more about excavators.



[eqtoday.co/Excavators](http://eqtoday.co/Excavators)



## LIUGONG



Liugong uses well-accepted componentry, such as Cummins engines and Kawasaki hydraulics, and integrates them into chassis across its excavator line. Liugong North America also has a parts support hub near Houston, Texas, and an active and growing dealer network to support and grow contractors' businesses.

Model No.	Engine HP (net)	Operating Weight (lbs.)	Std. Bucket Capacity (cu. yds.)	Breakout Force (lbs.)	Max. Digging Depth (ft. in.)	Max. Reach at Grade/Ground Level (ft. in.)
9018F	18	3,900-4,600	0.60	3,600	8' 0" to 7' 6"	13' 1" to 12' 8"
9027FZTS	22	5,900-6,500	0.65	4,500	9' 4"	15' 3"
9035EZTS	24	8,500-9,400	0.14	6,700	10' 1"	18' 8"
9051FZTS	48	11,420-12,700	0.18	8,300	11' 5"	18' 11"
9057FZTS	48	12,600-14,000	0.21	9,900	11' 11"	19' 10"
909ECR	59	19,200	0.37	14,200	14' 9"	23' 9"
913FCR	94	32,400	0.65	21,800	19' 4"	28' 2"
915FCR	122	34,000	0.72	21,800	19' 6"	28' 4"
922F	158	50,300	1.44	34,300	22' 0"	32' 5"
926F	213	58,400	1.7	40,200	22' 8"	33' 9"
933F	235	75,600	1.8	45,600	23' 11"	34' 11"
936F	314	85,800	2.3	70,900	24' 1"	36' 5"
950E	400	108,500	2.9	59,100	25' 8"	38' 9"
995F	608	209,000	7.3	111,500	23' 7"	41' 0"

## MECALAC



Mecalac offers its MWR Series of wheeled excavators to the North American market. With four-wheel steering, the 75-hp machines feature a turn radius 2.5 times more compact than a traditional wheeled excavator and can lift as much as 3 tons up to 9.8 ft.

Model No.	Engine HP (net)	Operating Weight (lbs.)	Std. Bucket Capacity (cu. yds.)	Breakout Force (lbs.)	Max. Digging Depth (ft. in.)	Max. Reach at Grade/Ground Level (ft. in.)
6MCR	75	12,600-13,600	0.10-0.64	9,666	11' 1"	21'
8MCR	75	15,900-16,755	0.10-0.69	11,240	12' 2"	22' 1"
10MCR	75	20,723-22,046	0.10-0.98	13,500	13' 1"	24' 7"
15MC	136	32,584-34,017	0.12-1.31	18,370	16' 4"	28' 10"
7MWR	75	15,300-16,210	0.10-0.71	9,666	9' 11"-10' 10"	20' 5"-25' 5"
9MWR	75	19,850	0.10-0.75	11,240	11' 6"	22'
11MWR	75	22,050-24,250	0.10-1.1	13,500	12' 6"	24' 7"
15MWR	136	31,345-34,079	0.12-1.31	18,370	14' 11"-15' 9"	28' 10"
12 MTX	115	21,384.000	0.2-1	13,820	13' 5"	23' 5"

## TAKEUCHI



Takeuchi manufactures 18 compact excavators for distribution throughout North America, ranging from the TB210R (just 2,535 pounds.) to the TB2150R (34,435 pounds when equipped with a cab). Takeuchi introduced its first electric model, the TB20e, in 2022. Other newer models include two short-tail-swing excavators, the TB335R (3.5-ton class) and the TB350R (5-ton class).

Model No.	Engine HP (net)	Operating Weight (lbs.)	Std. Bucket Capacity (cu. yds.)	Breakout Force (lbs.)	Max. Digging Depth (ft. in.)	Max. Reach at Grade/Ground Level (ft. in.)
TB210R	11.5	2,535	0.03	3,642	5' 9"	10' 6.8"
TB216	14.5	3,900	0.05	4,226	7' 10"	13' 2.9"
TB216H (hybrid)*	14.5/14.2	4,277	0.05	4,226	7' 10"	13' 2.9"
TB20e**	36.7 kWh + 8.7 kWh electric motor peak power	4,255	0.05	4,226	7' 10"	13' 2.9"
TB225	18.2	4,995	0.08	5,261	8' 5.6"	13' 11.3"
TB230	23.6	6,195	0.09	6,205	9' 3.6"	15' 5.4"
TB235-2	23.6	7,418-7,639	0.14	9,172	10' 7.8"	16' 10"
TB240	33.9	8,555-8,975	0.16	10,431	11' 4.4"	17' 9.6"
TB250-2	37.5	10,955-11,290	0.18	10,431	12' 4.8"	19' 7.6"
TB257FR	49.9	12,675-12,930	0.18	10,431	12' 9.4"	19' 11.4"
TB260	45.1	12,125-12,645	0.22	12,387	12' 9.4"	20' 1.4"
TB370	54.4	14,850	0.24	14,613	13' 4.8"	21' 6.5"
TB280FR	66.5	18,810	0.32	16,344	14' 10.8"	23' 1.4"
TB290	66.5	18,520	0.32	18,322	15'	23' 11.2"
TB2150	113.9	33,280	0.59	22,256	17'10.4"	28' 1.2"
TB2150R	113.9	33,995	0.59	22,256	19' 9.4"	28'5.1"
TB335R	23.6	7,970-8,310	0.14	9,172	10'6.2"	17' 4.9"
TB350R	41.7	10,980-11,235	0.18	10,431	11'8.8"	19'5.2"

\*Diesel/Electric

\*\*Electric

Changes to HP are due to net HP rating per ISO9249/SAEJ1349, except for TB2150/TB2150R which are net HP rating per ISO14396

## LINK-BELT EXCAVATORS



Link-Belt Excavators X4S Series is tough on dirt yet easy on fuel with its Custom Flow Balance and four selectable work modes. The spacious cab features a 10-inch monitor and a WAVES 270-degree camera system. Plus, maintenance is simplified with an easy-to-access hydraulic oil sampling port.

Model No.	Engine HP (net)	Operating Weight (lbs.)	Std. Bucket Capacity (cu. yds.)	Breakout Force (lbs.)	Max. Digging Depth (ft. in.)	Max. Reach at Grade/Ground Level (ft. in.)
75X3 MSR	54	17,400	0.24-0.71	12,800	15' 2"	22' 2"
75X3 MSR Offset Boom	54	18,300	0.24-0.45	12,800	15' 1"	21' 10"
80X3 MSR Swing Boom	54	18,900	0.24-0.71	12,800	15' 4"	24' 4"
130X4 LC	102	29,100	0.42-0.98	21,400	19' 1"	28' 4"
130X4 DZ	102	30,500	0.42-0.98	21,400	19' 1"	28' 4"
145X4 LC MSR	102	32,100	0.42-0.98	21,400	19' 9"	28' 3"
145X4 DZ MSR	102	33,600	0.42-0.98	21,400	19' 9"	28' 3"
170 X4S	120	39,000	0.50-1.35	26,527	19' 11"	29'2"
190 X4S	120	41,700	0.50-1.35	26,527	19' 10"	29'1"
220 X4S	160	48,900	0.58-1.75	34,600	21' 10"	31'11"
220X4S Long Front	160	52,000	0.5-0.98	14,600	39' 5"	51'2"
210X4 HD	160	56,900	0.64-1.75	34,600	17' 3"	31'8"
245X4 LC MSR	160	56,900	0.61-1.75	34,600	21' 10"	31' 9"
245X4 DZ MSR	160	58,100	0.61-1.75	34,600	21' 10"	31' 9"
260X4S Long Front	177	63,900	0.5-0.95	17,300	47' 9"	60'1"
250X4 HD	177	68,400	0.79-2.43	39,570	17' 3"	33' 0"
260 X4S	177	57,300	0.67-1.88	39,570	22' 8"	33'2"
300 X4S	253	67,700	0.80-2.43	42,780	23' 4"	34'5"
300X4 HD	207	73,200	0.79-2.43	42,780	18' 10"	34' 4"
355X4S MSR	205	78,709	0.79-2.43	42,780	24' 5"	36' 4"
350X4	268	82,400	1.08-2.93	56,160	26' 9"	38' 5"
350X4 Long Front	268	88,600	0.65-1.4	29,000	46' 3"	61' 3"
490X4 Fixed Frame	362	109,800	1.37-4.04	60,700	30' 2"	42' 1"
490X4 Expandable Frame	362	112,900	1.37-4.04	60,700	29' 8"	42' 9"
750X4	512	158,300	1.78-5.86	75,090	32' 4"	46' 8"
750X4 ME	512	159,600	1.78-5.86	82,280	23' 7"	37' 6"



# SANY



SANY America's swing boom excavators operate well in confined spaces. Offered in different machine configurations, these mini and small excavators perform well in many applications like landscaping, utilities, general construction, sewer and land management. All models feature standard auxiliary lines to operate powered attachments. When you need a smaller footprint, SANY's small, fixed boom excavators are the ideal solution.

Model No.	Engine HP (net)	Operating Weight (lbs.)	Std. Bucket Capacity (cu. yds.)	Breakout Force (lbs.)	Max. Digging Depth (ft. in.)	Max. Reach at Grade/Ground Level (ft. in.)
SY16C	18.2	4,112	0.04-0.07	3,732	7' 9"	13' 1"
SY26U	19.4	6,085	0.04-0.17	6,272	9' 3"	15' 11"
SY35U (cab)	23.3	8,499-8,367	0.07-0.22	6,385	10' 3"	18'
SY50U	37.1	11,860	0.09-0.28	7,846	11' 3"	19' 3"
SY60C	55.1	133,228	0.12-0.38	10,116	13'	20' 9"
SY75C	54	16,050	0.12-0.52	11,915	14' 7"	21' 4"
SY80U	66.4	19,401	0.10-0.49	16,343	14' 10.5"	23' 11"
SY95C	66.4	20,238	0.12-0.74	14,365	14' 2"	22' 3"
SY135C	103.9	32,783	0.24-1.06	20,075	17' 11"	27' 2"
SY155U	103.9	35,274	0.24-1.06	23,155	19' 9"	28' 10"
SY215C LC	164 gross	51,919	0.55-1.85	28,551	21' 8"	33' 10"
SY225C LC	164 gross	54,013	0.55-1.85	28,551	21' 8"	33' 10"
SY265C LC	194 gross	59,525	0.64-2.09	42,039	22'	33' 7"
"SY265C LC (long reach)"	190 gross	69,446	0.64-0.80	19,334	43' 8"	57' 9"
SY335C LC	280 gross	74,075	0.86-2.4	45,861	22' 4"	35' 8"
SY365C LC	275 gross	80,910	1.07-3.17	43,163	23' 11"	36' 5"
SY385C	314 gross	85,318	1.47-3.16	52,875	26' 2"	38' 2"
SY500H	400 gross	120,152	1.23-4.05	61,822	25' 3"	39' 5"
SY750H	524 gross	173,063	4.5-6.5	92,172	24' 10"	39' 8"

# SUNWARD



SUNWARD excavators boast many useful features. The range starts at the 1-ton mini diggers to a large 36-ton excavator on either wheels or tracks with conventional or zero-tail design. There is a product in this range to suit every jobsite need.

Model No.	Engine HP (net)	Operating Weight (lbs.)	Std. Bucket Capacity (cu. yds.)	Breakout Force (lbs.)	Max. Digging Depth (ft. in.)	Max. Reach at Grade/Ground Level (ft. in.)
SWE10FED	76.8 V - Electric Unit	2,227	0.03	2,113	4' 9"	8' 11"
SWE18UF	18	4,145	0.052	5,103	7' 3"	13' 5"
SWE20FED	76.8 V - Electric Unit	3,925	0.052	4,721	7' 10"	13' 3"
SWE20F	18	4,277	0.052	5,103	7' 10"	13' 3"
SWE25UF	19.6	5,843	0.1	5,395	9' 4"	15' 8"
SWE35UF	24.4	8,489	0.14	7,149	10' 3"	17' 3"
SWE50UF	39.8	11,797	0.18	7,643	11' 1"	19' 2"
SWE60UF	48.2	12,723	0.23	10,566	12' 2"	20'
SWE90UF	62.8	19,290	0.34	14,275	14' 11"	25' 10"
SWE155F	126.4	33,951	0.78	22,480	18' 2"	26' 9"
SWE155UF	126.4	36,383	0.79	22,481	18' 1"	27'
SWE155FW	156.4	36,383	0.79	22,548	17' 1"	27' 6"
SWE215F	175.4	49,163	1.3	34,870	21' 9"	32'
SWE335F	280	74,075	2.22	45,109	23'	34'

# KOBELCO



KOBELCO Construction Machinery USA offers a full line of crawler excavators that include zero-tail-swing, compact, standard, long-reach and demolition models to meet every challenge. KOBELCO provides engine efficiency and productivity, plus operator controls and comfort. KOBELCO excavators bring more features as standard and are built to bring performance to help get the job done.

Model No.	Net HP	Operating Weight (lbs.)	Std. Bucket Capacity (cu. yds.)	Bucket Breakout Force (lbs.)	Max. Digging Depth (ft. in.)	Max. Reach at Grade/Ground Level (ft. in.)
SK17SR-6E	14.5	3,681	0.065	3,417	7' 3"	12' 3"
SK26SR-7	23.1	6,504	0.09	4,680	9' 2"	16' 1"
SK35SR-7	23.1	9,340	0.13	9,960	11' 0"	18' 0"
SK45SRX-7	37	10,648	0.11	11,232	11' 3"	18' 8"
SK55SRX-7	37	12,147	0.12	11,232	13' 6"	20' 9"
SK75SR-7	70	18,700	0.14-0.37	15,900	15' 0"	22' 2"
SK75SR-7 Offset Boom	70	19,555	0.14-0.37	15,900	14' 1"	20' 10"
SK85CS-7	70	20,100	0.14-0.37	15,900	14' 7"	24' 1"
SK130LC-11	96	32,800	0.30-0.88	24,800	19' 7"	28' 3"
SK140SRLC-7	105	32,800	0.30-0.88	24,800	19' 7"	28' 5"
SK140SRLC-7 Offset Boom	105	33,700	0.30-0.88	22,000	17' 2"	25' 3"
ED160BR-7 Blade Runner	105	37,000	0.30-0.88	24,800	19' 0"	28' 3"
SK170LC-11	123	39,500	0.6-1	28,300	21' 4"	30' 7"
SK210LC-11	160	49,600	0.63-1.8	35,300	23' 10"	33' 4"
SK230SRLC-7	164	57,100	0.63-1.8	29,700	21' 7"	31' 3"
SK260LC-11	194	60,200	0.875-2.25	42,000	25' 2"	35' 6"
SK270SRLC-7	164	61,100	0.63-1.8	35,300	23' 1"	33' 0"
SK300LC-11	265	69,200	0.75-1.875	46,800	26' 7"	37' 10"
SK350LC-11	265	84,200	0.875-2.75	56,200	26' 11"	38' 8"
SK380SRLC-7	265	84,200	0.875-2.75	46,800	24' 9"	37' 2"
SK520LC-11	463	121,000	1.50-4.26	72,200	30' 3"	43' 3"
SK210LC-11 High & Wide	160	55,100	0.63-1.80	35,300	22' 8"	33' 2"
SK260LC-11 High & Wide	194	66,400	0.875-2.25	42,000	24' 1"	35' 4"
SK300LC-11 High & Wide	265	74,700	0.875-1.875	46,800	25' 7"	37' 8"
SK390LC-11 High & Wide	265	84,000	0.875-2.75	56,200	25' 11"	38' 6"
SK210LC-11 Long Reach	160	53,400	0.6	19,800	39' 5"	51' 7"
SK260LC-11 Long Reach	194	62,600	0.6	19,800	48' 4"	60' 6"
SK300LC-11 Long Reach	265	79,160	0.62	22,700	48' 10"	62' 9"

# HEVI



HEVI's electric excavators deliver rugged performance, versatility and durability with emission and cost savings. In 2025, HEVI will introduce a tracked version of the GEX-8000 attachment. The tracked excavator will offer enhanced mobility and stability for the most demanding jobs..

Model No.	Engine HP (net)	Operating Weight (lbs.)	Std. Bucket Capacity (cu. yds.)	Breakout Force (lbs.)	Max. Digging Depth (ft. in.)	Max. Reach at Grade/Ground Level (ft. in.)
GEX-8000 Electric	62	18,739	0.34	11,240	7' 7"	19'



# YANMAR



Yanmar's current mini excavator line features nine models. The lineup includes zero- and ultra-tight-tail-swing excavators that have either no protrusion beyond the track or minimal protrusion. Yanmar backs its mini excavators with a four-year/4,000-hour warranty. Additionally, Yanmar's SmartAssist remote telematics system comes standard on all excavators free for the first five years.

Model No.	Engine HP (net)	Operating Weight (lbs.)	Std. Bucket Capacity (cu. yds.)	Breakout Force (lbs.)	Max. Digging Depth (ft. in.)	Max. Reach at Grade/ Ground Level (ft. in.)
SV08-1D	10.3	2,348	-	2,360	5' 4"	8' 11"
VI07-1E	14.5	4,023	-	3,474	7' 7"	11' 3"
VI025-6B	20.4	5,908	-	4,788	10'	14' 9"
VI035-6A	24.4	8,214	-	5,643	11' 3"	16' 9"
SV40	39	9,515	-	7,209	11' 10"	17' 6"
VI050-6A	39	10,792	-	8,206	12' 3"	18' 8"
VI055-6A	47.6	12,247	-	9,419	13' 6"	19' 10"
VI080-7	67	18,409	-	10,813	14' 3"	23' 9"
SV100-7	72	21,671	-	12,027	14' 11"	25' 3"

# VOLVO



Volvo's new generation of excavators was built to give customers an edge in productivity, profitability and comfort. The lineup's biggest update in two decades brings up to 15% lower fuel consumption; an upgraded hydraulic system; and improvements to the cab including a new seat, more precise controls and even a wireless phone charger.

Model No.	Engine HP (gross)	Operating Weight (lbs.)	Std. Bucket Capacity (cu. yds.)	Breakout Force (lbs.)	Max. Digging Depth (ft. in.)	Max. Reach at Grade/ Ground Level (ft. in.)
EC18 Electric	16.8 (12.5 kW)	4,310	0.02-0.07	2,900	8' 10"	13' 1"
ECR18 Electric	16.8 (12.5 kW)	3,957	0.02-0.07	2,900	8' 11"	13' 6"
ECR25 Electric	14.7 kW (20 hp)	6,018	0.04-0.14	5,020	9' 9"	15' 1"
EC230 Electric	214 (160 kW)	50,910-54,200	1.24-2.03	33,500	22' 2"	32' 1"
ECR18E	16	3,748	0.02-0.07	2,900	8' 11"	13' 6"
EC20E	16	4,332	0.04-0.1	4,107	9' 4"	14'
ECR25D	21	5,490	0.04-0.16	5,020	9' 9"	15' 1"
EC27D	21	6,019	0.04-0.16	5,528	10' 2"	15' 4"
EC37	24.8	8,345	0.07-0.2	7,987	11' 11"	17' 9"
ECR40	24.8	8,785	0.07-0.2	7,987	12' 3"	18' 11"
ECR50	42	11,133	0.19	8,134	13' 7"	20' 2"
ECR58	48	12,875	0.19	9,422	13' 11"	20' 6"
EC60E	59	12,740	0.09-0.35	9,720	13' 1"	20' 6"
ECR88D	57	19,886	0.1-0.44	12,770	14' 10"	23' 7"
EC140E	121	31,220-32,500	0.75-1.24	21,720	19' 11"	28' 7"
ECR145E	121	32,900-34,180	0.75-1.24	21,720	19' 9"	28' 7"
EC160E	148	38,890-40,790	0.88-1.5	27,410	21' 3"	30' 2"
EC200E	154	46,980-49,080	0.90-1.54	33,500	22' 3"	32' 3"
EC210	154	48,240-50,970	0.90-1.54	33,500	22' 5"	32' 3"
EC220E	173	47,280-50,140	1.24-2.03	33,500	22' 2"	32' 1"
EC230	173	50,150-52,460	1.24-2.03	33,500	22' 2"	32' 1"
ECR235E	173	54,180-56,840	1.24-2.03	33,590	22' 2"	31' 11"
EC250E	225	59,160-61,540	1.54-2.65	40,710	23' 2"	33' 4"
EC250E Hybrid	225	60,040-62,420	1.54-2.65	40,710	23' 2"	33' 4"
EC300E	253	67,560-71,750	1.63-2.78	46,450	24' 1"	34' 6"
EC300E Hybrid	253	68,620-72,150	1.63-2.78	46,450	24' 1"	34' 6"
EC300E Straight Boom	253	75,519-78,448	6,850*	46,535	20' 1"	37' 10"
EC350E	308	79,950-84,800	3.2	59,665 (ISO)	27' 2"	38' 3"
ECR355E	241	75,292-78,057	1.63-2.78	46,985	22' 10"	34' 3"
EC370	339	83,680-87,470	1.14-3.19	44,512	26' 9"	38' 3"
EC380E	308	84,570-89,840	3.7	59,665 (ISO)	27' 2"	38' 3"
EC380E Hybrid	308	85,450-90,720	3.7	59,665 (ISO)	27' 2"	38' 3"
EC380E HR	308	117,528-120,482	6,614*	--	--	75' 8"***
EC380E Straight Boom	308	99,640-102,560	8,818 (Processor)*	54,560	22' 5"	40' 7"
EC400	339	86,810-90,980	1.24-3.79	54,650	27' 2"	38'11"
EC480E	381	105,540-111,180	4.5	69,825 (ISO)	30' 5"	43' 2"
EC480E HR	381	146,795-150,113	7,716*	--	--	92' 4"***
EC500	418	109,520-116,290	2.01-5	68,960	29' 1"	42' 11"
EC530E	456	115,830-124,010	5	74,000	27'	40' 9"
EC550E	456	120,000-125,600	6	74,000	27'	40' 9"
EC750E	527	161,190-166,040	8.5	86,110	29' 8"	44' 4"
EC750E HR	527	227,664-229,344	7,937 (optional 11,023)*	--	--	118' 1" (optional 85' 4")***
EC950F	603	201,227-209,020	10	107,459	29' 4"	45' 1"
EW60E	63	13,050	0.09-0.35	9,734	11' 10"	21' 6"
EW130E	119	28,440-31,306	0.35-0.86	18,435	16' 7"	24' 4"
EW150E	141	33,951-39,462	0.95	24,392	18' 9"	28' 11"
EW160E	156	35,714-40,124	1.02	28,325	20' 5"	31'
EW170E	154	39,573-42,329	0.9	28,326	18' 9"	28' 11"
EW180E	175	40,124-44,753	1.14	30,574	20'	31' 11"
EW200E MH	169	48,722-50,376	--	--	--	33'
EW220E	173	48,898	1.3	29,675	20'	31' 11"
EW240E MH	173	57,320	--	--	--	36' 11"

\*Max Tool Weight (lbs.)

\*\*Max Tool Height (ft. in.)

# WACKER NEUSON



Wacker Neuson offers 12 excavator models ranging from a mini 1-ton to a larger, but still compact 14-ton model. The rugged and reliable machines offer excellent breakout force for the toughest conditions and provide the power, maneuverability and stability to get the job done in less time and with less effort.

Model No.	Engine HP (net)	Operating Weight (lbs.)	Std. Bucket Capacity (cu. yds.)	Breakout Force (lbs.)	Max. Digging Depth (ft. in.)	Max. Reach at Grade/ Ground Level (ft. in.)
803 Dual power	15.5	2,319-2,451	0.01-0.03	2,021	5' 9"	9' 11"
EZ17	17.9	3,801-4,299	0.03-0.07	4,609	8' 2"	13' 2"
ET20	17.9	4,420-5,125	0.03-0.07	4,226	8' 10"	13' 10"
EZ26	19.6	5,412-7,403	0.07-0.25	5,081	9' 2"	15' 4"
EZ36	24.5	8,197-10,902	0.07-0.25	7,868	11' 6"	18' 6"
ET42	43.6	8,889 - 11,477	0.14-0.20	6,722	11' 6"	18' 3"
EZ50	43.6	10,686-12,908	0.14-0.20	7,014	12'	19' 6"
ET58	44.8	10,619-12,412	0.14-0.20	6,474	13' 1"	20' 2"
ET65	56.4	13,399-16,221	0.11-0.36	11,398	13' 6"	21'
ET90 (mono boom)	69.2	19,202-23,161	0.13-0.48	16,591	15' 2"	24' 7"
ET90 (triple boom optional)	69.2	19,614-23,161	0.13-0.48	16,591	15' 4"	25' 5"
EW65 (triple boom)	56.4	14,892-16,928	0.11-0.36	11,398	12' 9"	22'
EW100 (triple boom)	74.3	21,351-26,579	0.13-0.48	12,162	13' 11"	25' 11"
ET145	73.8	34,284-38,045	0.33-1.05	20,458	18'	28'



# FORCONSTRUCTIONPROS.COM/EQUIPMENT



IRONMARKETS is a leading business-to-business media and business intelligence company with a portfolio of renowned brands in heavy construction, asphalt, concrete, paving, rental, sustainability, landscape, manufacturing, logistics and supply chain markets. IRONMARKETS delivers relevant, cutting edge content to its audiences through its industry-leading digital properties, trade shows, videos, magazines, webinars and newsletters. It also provides advertisers the analytics, data and ability to reach their target audience.