



## BX Series

BX23S

### Easy operation, superior comfort, and simple operation.

- › Kubota's Swift-Tach Loader allows for quick and easy removal and installation of the front loader without tools and without getting off the operator station
- › The Kubota Swift-Connect Backhoe on the BX23S is designed to match perfectly with the tractor and loader: not only designed to tackle tough digging jobs, but also designed to be versatile, the BX23S can be converted from a backhoe to a tractor with a 3-point hitch quickly, easily, and without tools
- › With an optional Category I 3-point hitch, optional mid-mount mower decks, and an available front hitch, the BX Series can be equipped with an implement to quickly and easily handle most any task
- › The BX23S has a deluxe high-back seat with armrests, tilt steering, and reversible seat for comfort when operating the tractor, loader, or backhoe
- › The ROPS operator opening has been widened, giving the operator additional room and comfort when operating the backhoe
- › Equipped with a Hydrostatic Transmission (HST), the BX Series tractors are easy to use—simply press the pedal forward to go forward, press the pedal backwards for reverse—our treadle pedal system will have even first-time owners operating like professionals in no time
- › Got snow? The Kubota Heated Cab is a great dealer-installed option to add to your BX Series to improve comfort and protect yourself during those cold winter months

## BX Series

### BX23S

Engine Type	Kubota, liquid-cooled, diesel, 3-cylinder
Horsepower (gross)*	21.6
Horsepower (PTO)*	17.7
Displacement (cu. in.)	54.8
Length (w/ 3-point)	99.0" w/ front guard
Width (min. tread)	45.1"
Height (w/ ROPS)	86.2"
Wheelbase	55.1"
Ground Clearance (front axle)	6.5"
Speed (mph) (front/reverse)	0–8.4 / 0–6.5
Transmission	HST, high-low gear shift (2 forward/reverse)
Tractor Weight (lbs.)	1,598

#### KEY ATTACHMENTS

Front Loader	Included
Backhoe	Included
Mid-Mount Mower	54", 60"
Easy-Over Mower	54", 60"

#### FRONT LOADER SPECIFICATIONS

	LA340 Pin-on Style Bucket	LA340S Two Lever Quick Attach Bucket
Maximum Lift Height	71"	
Lift Capacity at Pivot Pin (1500 mm height) (lbs.)	820	699
Breakout Force (bucket pivot pin) (lbf.)	1,407	1,286

#### BACKHOE SPECIFICATIONS

### BT603

Digging Depth	6' 2"
Transport Height	67.7"
Reach from Swing Pivot	102.8"
Bucket Size	8", 12", 16"
Thumb	Optional – Mechanical

MOWER SPECIFICATIONS	MID-MOUNT		EASY-OVER	
Cutting Width	54"	60"	54"	60"
Discharge	Side			
Mounting Method	Suspended			
Adjustment of Cutting Height	Dial			

\* SAE J1995